



## MAL210213152E3 Information

Heisener.com

Part Number MAL210213152E3

Manufacturer Vishay BC Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 1500UF 20% 250V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MAL210213152E3 Specifications**

Manufacturer Part Number         MAL210213152E3           Manufacturer         Vishay BC Components           Category         Capacitors           Package         Radial, Can - Screw Terminals           Scries         102 PHR-ST           Capacitance         1500µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         90 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         5.4A @ 100Hz           Ripple Current - High Frequency         -           Ripple Current - High Frequency         1.378 "Dia (35.00mm)           Lead Spacing         0.504" (12.80mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         4.280" (108.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	*	
Category         Capacitors           Package         Radial, Can - Screw Terminals           Series         102 PHR-ST           Capacitance         1500µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         90 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         5.4A @ 100Hz           Ripple Current - High Frequency         -           Impedance         58 mOhms           Lead Spacing         0.504" (12.80mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         4.280" (108.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer Part Number	MAL210213152E3
Package         Radial, Can - Screw Terminals           Series         102 PHR-ST           Capacitance         1500μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         90 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         5.4A @ 100Hz           Ripple Current - High Frequency         -           Impedance         58 mOhms           Lead Spacing         0.504" (12.80mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         4.280" (108.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	Vishay BC Components
PackageRadial, Can - Screw TerminalsSeries102 PHR-STCapacitance1500µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.4A @ 100HzRipple Current - High Frequency-Impedance58 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.280" (108.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         102 PHR-ST           Capacitance         1500μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         90 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         5.4A @ 100Hz           Ripple Current - High Frequency         -           Impedance         58 mOhms           Lead Spacing         0.504" (12.80mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         4.280" (108.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance         1500µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         90 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         5.4A @ 100Hz           Ripple Current - High Frequency         -           Impedance         58 mOhms           Lead Spacing         0.504" (12.80mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         4.280" (108.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 5.4A @ 100Hz  Ripple Current - High Frequency -  Impedance 58 mOhms  Lead Spacing 0.504" (12.80mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 4.280" (108.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	102 PHR-ST
Voltage - Rated250 VESR (Equivalent Series Resistance)90 mOhm @ 100 HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.4A @ 100 HzRipple Current - High Frequency-Impedance58 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.280" (108.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	1500μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  5.4A @ 100Hz  Ripple Current - High Frequency  Impedance  58 mOhms  Lead Spacing  0.504" (12.80mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Frequency  Fipple Current - High Frequency  S8 mOhms  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  10000 Hrs @ 85°C  -40°C ~ 85°C  Foliar  Foliar  General Purpose  5.4A @ 100Hz  5.4A @ 100Hz  1.378" Dia (35.00mm)  4.280" (12.80mm)  Chassis Mount  Radial, Can - Screw Terminals	Voltage - Rated	250V
Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 5.4A @ 100Hz  Ripple Current - High Frequency -  Impedance 58 mOhms  Lead Spacing 0.504" (12.80mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 4.280" (108.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 5.4A @ 100Hz  Ripple Current - High Frequency -  Impedance 58 mOhms  Lead Spacing 0.504" (12.80mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 4.280" (108.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications  General Purpose  Ripple Current - Low Frequency  Fipple Current - High Frequency  Impedance  S8 mOhms  Lead Spacing  0.504" (12.80mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  4.280" (108.70mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  58 mOhms  Lead Spacing  0.504" (12.80mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  4.280" (108.70mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 58 mOhms Lead Spacing 0.504" (12.80mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 4.280" (108.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance58 mOhmsLead Spacing0.504" (12.80mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.280" (108.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	5.4A @ 100Hz
Lead Spacing0.504" (12.80mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)4.280" (108.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 4.280" (108.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	58 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	0.504" (12.80mm)
Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.280" (108.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### MAL210213152E3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MAL210213152E3 Payment Methods**





















### **MAL210213152E3 Shipping Methods**













If you have any question about MAL210213152E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com