



MAL210225152E3 Information

Heisener.com

Part Number MAL210225152E3

Manufacturer Vishay BC Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1500UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAL210225152E3 Specifications

Manufacturer Part Number MAL210225152E3 Manufacturer Vishay BC Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 102 PHR-ST Capacitance 1500µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 102 PHR-ST Capacitance 1500µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 10874 (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	MAL210225152E3
Package Radial, Can - Screw Terminals Series 102 PHR-ST Capacitance 1500μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	Vishay BC Components
PackageRadial, Can - Screw TerminalsSeries102 PHR-STCapacitance1500µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)99 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension1.969" Dia (50.00mm)Height - Seated (Max)4.362" (110.80mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series 102 PHR-ST Capacitance 1500μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raidla, Can - Screw Terminals	Series	102 PHR-ST
Voltage - Rated350VESR (Equivalent Series Resistance)99 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency7A @ 100HzRipple Current - High Frequency-Impedance70 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension1.969" Dia (50.00mm)Height - Seated (Max)4.362" (110.80mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	1500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency -Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 85°C -40°C ~ 85°C -40°	Voltage - Rated	350V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	99 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 70 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance70 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension1.969" Dia (50.00mm)Height - Seated (Max)4.362" (110.80mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	7A @ 100Hz
Lead Spacing0.874" (22.20mm)Size / Dimension1.969" Dia (50.00mm)Height - Seated (Max)4.362" (110.80mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 1.969" Dia (50.00mm) Height - Seated (Max) 4.362" (110.80mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	70 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	1.969" Dia (50.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.362" (110.80mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

MAL210225152E3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL210225152E3 Payment Methods



















MAL210225152E3 Shipping Methods













If you have any question about MAL210225152E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com