

MAL212310109E3

est a Quote

MAL212310109E3 Information

	Part Number	MAL212310109E3	
/	Manufacturer	Vishay BC Components	
www.heisper.com	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 10UF 20% 35V AXIAL	- 43
	Package	Axial, Can	Ē
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAL212310109E3 Specifications

ManufacturerVishay BC ComponentsCapacitorsCapacitorsAtuninum Electrolytic CapacitorsPackageAxial, CanSeriesSAL-A 123Capacitance10µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.2000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - High Frequency-Impedance2.5 OhmsLided Spacing0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseXail, Can	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageAxial, CanPackageSAL-A 123Capacitance10µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Manufacturer Part Number	MAL212310109E3
Aluminum Electrolytic CapacitorsPackageAxial, CanSeriesSAL-A 123Capacitance10μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Lad Spacing-Siz / Dimension0.299° Dia x 0.803° L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseAxial, Can	Manufacturer	Vishay BC Components
PackageAxial, CanSeriesSAL-A 123Capacitance10µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - High Frequency-Impedance2.5 OhmsLiad Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Package / CaseAxial, Can	Category	Capacitors
SeriesSAL-A 123Capacitance10µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Lingdance2.5 OhmsLead Spacing0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeThrough HolePackage / CaseAxial, Can		Aluminum Electrolytic Capacitors
Capacitance 10μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 10 Ohm Lifetime @ Temp. 20000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization - Applications General Purpose Ripple Current - Low Frequency - Impedance 2.5 Ohms Lead Spacing - Size / Dimension 0.299" Dia x 0.803" L (7.60mm x 20.40mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Axial, Can	Package	Axial, Can
Tolerance±0%Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency-Lead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Pockage / CaseAxial, Can	Series	SAL-A 123
Voltage - Rated35VESR (Equivalent Series Resistance)10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Argulance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeAxial, Can	Capacitance	10µF
Constraint10 OhmLifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Bipple Current - High Frequency-2.5 Ohms2.5 OhmsLead Spacing0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Pounting TypeAxial, Can	Tolerance	±20%
Lifetime @ Temp.20000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarization-ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Voltage - Rated	35V
And Solution	ESR (Equivalent Series Resistance)	10 Ohm
Polarization-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HoleAckage / CaseAxial, Can	Lifetime @ Temp.	20000 Hrs @ 125°C
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency-Ripple Current - High Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Polarization	-
Ripple Current - High Frequency-Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Applications	General Purpose
Impedance2.5 OhmsLead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Ripple Current - High Frequency	-
Size / Dimension0.299" Dia x 0.803" L (7.60mm x 20.40mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Impedance	2.5 Ohms
Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Lead Spacing	-
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Size / Dimension	0.299" Dia x 0.803" L (7.60mm x 20.40mm)
Mounting TypeThrough HolePackage / CaseAxial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

MAL212310109E3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL212310109E3 Payment Methods



MAL212310109E3 Shipping Methods



If you have any question about MAL212310109E3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com