



MAL213450229E3 Information

Heisener.com

For Reference Only

Part Number MAL213450229E3

Manufacturer Vishay BC Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 35V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAL213450229E3 Specifications

Manufacturer Part Number MAL213450229E3 Manufacturer Vishay BC Components Category Capacitors Package Radial, Can Series 134 RLP 5 Capacitance 22µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp, 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		
Category Capacitors Package Radial, Can Series 134 RLP 5 Capacitance 22µF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	MAL213450229E3
PackageRadial, CanSeries134 RLP 5Capacitance22μFTolerance±20%Voltage - Rated35 VESR (Equivalent Series Resistance)-Lifetime @ Temp.1500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency-Impedance11 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Vishay BC Components
Package Radial, Can Series 134 RLP 5 Capacitance 22µF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series 134 RLP 5 Capacitance 22µF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	134 RLP 5
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.1500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency-Impedance11 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1500 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C General Purpose 40mA @ 120Hz 10hms - 11 Ohms 0.298" (2.50mm) 0.248" Dia (6.30mm) Through Hole Radial, Can	Voltage - Rated	35V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance I1 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1500 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency - Impedance 11 Ohms Lead Spacing 0.098" (2.50mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance11 OhmsLead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	40mA @ 120Hz
Lead Spacing0.098" (2.50mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	11 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.098" (2.50mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.236" (6.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

MAL213450229E3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL213450229E3 Payment Methods



















MAL213450229E3 Shipping Methods













If you have any question about MAL213450229E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com