



MAL214060471E3 Information

Heisener.com

For Reference Only

Part Number MAL214060471E3

Manufacturer Vishay BC Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 35V RADIAL

Package Radial, Car

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAL214060471E3 Specifications

Manufacturer Part Number MAL214060471E3 Manufacturer Vishay BC Components Category Capacitors Package Radial, Can Series 140 RTM Capacitance 470μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series 140 RTM Capacitance 470µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 173 mOhms Lead Spacing 10.197" (5.00mm) Size / Dimension 10.492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	MAL214060471E3
Package Radial, Can Series 140 RTM Capacitance 470µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer	Vishay BC Components
Package Radial, Can Series 140 RTM Capacitance 470μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series 140 RTM Capacitance 470μF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 470µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -55°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Series	140 RTM
Voltage - Rated35VESR (Equivalent Series Resistance)-Lifetime @ Temp.3000 Hrs @ 125°COperating Temperature-55°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency780mA @ 100HzRipple Current - High Frequency-Impedance73 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency -1 Impedance Tam Ohms Lead Spacing O.197" (5.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Polar 3000 Hrs @ 125°C -2 3000 Hrs @ 125°C -55°C ~ 125°C -10 3000 Hrs @ 125°C -51 3000 Hrs @ 125°C -6 300 Hrs @ 125°C -6 3000 Hrs @ 125°C -6 3000 Hrs @ 125°C -6 3	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 3000 Hrs @ 125°C -55°C ~ 125°C Polar -55°C ~ 125°C -50mA 0 100Hz -50mA 0 100Hz -50mB 0 .492" Dia (12.50mm) -50mB -	Voltage - Rated	35V
Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Ripple Current - High Frequency Ripple Current - High Frequency Polar Impedance T3 mOhms Lead Spacing D197" (5.00mm) Size / Dimension D492" Dia (12.50mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	3000 Hrs @ 125°C
Applications General Purpose Ripple Current - Low Frequency 780mA @ 100Hz Ripple Current - High Frequency - Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Operating Temperature	-55°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance To Mohms Lead Spacing To Mohms Lead Spacing To Mohms Lead Spacing To Mohms Lead Spacing To Mohms Lead Spacing To Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 73 mOhms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance73 mOhmsLead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	780mA @ 100Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.492" Dia (12.50mm)Height - Seated (Max)0.866" (22.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.492" Dia (12.50mm) Height - Seated (Max) 0.866" (22.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	73 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.492" Dia (12.50mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.866" (22.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

MAL214060471E3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL214060471E3 Payment Methods



















MAL214060471E3 Shipping Methods













If you have any question about MAL214060471E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com