



MAL215662332E3 Information

Heisener.com

Part Number MAL215662332E3 Manufacturer Vishay BC Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 3300UF 20% 80V SNAP

Radial, Can - Snap-In - 3 Lead **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAL215662332E3 Specifications

Manufacturer Part Number MAL215662332E3 Manufacturer Vishay BC Components Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series 156 PUM-SI Capacitance 3300µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series 156 PUM-SI Capacitance 3300µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	MAL215662332E3
Package Radial, Can - Snap-In - 3 Lead Series 156 PUM-SI Capacitance 3300μF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Manufacturer	Vishay BC Components
PackageRadial, Can - Snap-In - 3 LeadSeries156 PUM-SICapacitance3300µFTolerance±20%Voltage - Rated80VESR (Equivalent Series Resistance)155 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.92A @ 100HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series 156 PUM-SI Capacitance 3300μF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance 3300µF Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 80V ESR (Equivalent Series Resistance) 155 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Series	156 PUM-SI
Voltage - Rated80VESR (Equivalent Series Resistance)155 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.92A @ 100HzRipple Current - High Frequency-Impedance152 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	3300μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Riono Hrs @ 85°C -0000 Hrs	Tolerance	±20%
Lifetime @ Temp. 5000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Voltage - Rated	80V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	155 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	5000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.92A @ 100Hz Ripple Current - High Frequency - Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance 152 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	2.92A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	152 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

MAL215662332E3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL215662332E3 Payment Methods



















MAL215662332E3 Shipping Methods













If you have any question about MAL215662332E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com