



### MAL219816391E3 Information

Heisener.com

Part Number MAL219816391E3

Manufacturer Vishay BC Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 390UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MAL219816391E3 Specifications**

Manufacturer Part Number         MAL219816391E3           Manufacturer         Vishay BC Components           Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         198 PHR-SI           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         245 mOhm @ 100Hz           Lifetime @ Temp,         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		
Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Scries         198 PHR-SI           Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         245 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         175 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	MAL219816391E3
Package         Radial, Can - Snap-In - 3 Lead           Series         198 PHR-SI           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         245 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         175 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer	Vishay BC Components
PackageRadial, Can - Snap-In - 3 LeadSeries198 PHR-SICapacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)245 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance175 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series         198 PHR-SI           Capacitance         390µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         245 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         -           Ripple Current - High Frequency         -           Impedance         175 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance         390μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         245 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         175 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         2.047" (52.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 245 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.5A @ 100Hz  Ripple Current - High Frequency -  Impedance 175 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Series	198 PHR-SI
Voltage - Rated400VESR (Equivalent Series Resistance)245 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.5A @ 100HzRipple Current - High Frequency-Impedance175 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	390μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  2.5A @ 100Hz  Ripple Current - High Frequency  Impedance  175 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  175 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz Ripple Current - High Frequency - Impedance 175 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	245 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.5A @ 100Hz  Ripple Current - High Frequency -  Impedance 175 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.5A @ 100Hz Ripple Current - High Frequency - Impedance 175 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  175 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  2.047" (52.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 175 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance175 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	2.5A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 2.047" (52.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	175 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	2.047" (52.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### MAL219816391E3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MAL219816391E3 Payment Methods**



















# **MAL219816391E3 Shipping Methods**













If you have any question about MAL219816391E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com