



#### MAL219876221E3 Information

Heisener.com

For Reference Only

Part Number MAL219876221E3

Manufacturer Vishay BC Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 220UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MAL219876221E3 Specifications**

Manufacturer Part Number         MAL219876221E3           Manufacturer         Vishay BC Components           Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Scries         198 PHR-SI           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         434 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         1.56A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	•	
Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Scries         198 PHR-SI           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         434 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.56A @ 100Hz           Ripple Current - High Frequency         -           Impedance         280 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	MAL219876221E3
Package         Radial, Can - Snap-In - 3 Lead           Series         198 PHR-SI           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         434 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.56A @ 100Hz           Ripple Current - High Frequency         -           Impedance         280 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer	Vishay BC Components
PackageRadial, Can - Snap-In - 3 LeadSeries198 PHR-SICapacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)434 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.56A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series         198 PHR-SI           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         434 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.56A @ 100Hz           Ripple Current - High Frequency         -           Impedance         280 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         434 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.56A @ 100Hz           Ripple Current - High Frequency         -           Impedance         280 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 434 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.56A @ 100Hz  Ripple Current - High Frequency -  Impedance 280 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Series	198 PHR-SI
Voltage - Rated400 VESR (Equivalent Series Resistance)434 mOhm @ 100 HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.56A @ 100 HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.56A @ 100Hz  Ripple Current - High Frequency  Impedance  280 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.56A @ 100Hz  Ripple Current - High Frequency  Impedance  280 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.56A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	434 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.56A @ 100Hz  Ripple Current - High Frequency -  Impedance 280 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 1.56A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Polarization	Polar
Ripple Current - High Frequency Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.56A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	280 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### MAL219876221E3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MAL219876221E3 Payment Methods**



















## **MAL219876221E3 Shipping Methods**













If you have any question about MAL219876221E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com