



MAP110-1005 Information

Heisener.com

For Reference Only

N

Part Number MAP110-1005
Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5V 80W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAP110-1005 Specifications

Manufacturer Part Number MAP110-1005 Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MAP110 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Applications ITE (Commercial) Voltage - Isolation 4.242N (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MAP110 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Manufacturer Part Number	MAP110-1005
Package - Series MAP110 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Manufacturer	Bel Power Solutions
Package - Series MAP110 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MAP110 Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 5V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 16A Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Series	MAP110
Voltage - Input85 ~ 264 VACVoltage - Output 15VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)16APower (Watts)80W (110W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency80%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature Features Adjustable Output, Remote Sense, Universal Input Mounting Type Size / Dimension 5V Current - Output (Max) 16A 80W (110W Forced Air) 17E (Commercial) 4.242kV (4242V) 80% Commercial) 4.242kV (4242V) 80% Chassis Mount 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) - - - - - - - - - - - - -	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension - Courrent - Output (Max) - Chassis Mount - Chassis Moun	Voltage - Output 1	5V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 80W (110W Forced Air) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature O°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Current - Output (Max)	16A
Voltage - Isolation 4.242kV (4242V) Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Power (Watts)	80W (110W Forced Air)
Efficiency 80% Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Applications	ITE (Commercial)
Operating Temperature 0°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Isolation	4.242kV (4242V)
Features Adjustable Output, Remote Sense, Universal Input Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Efficiency	80%
Mounting Type Chassis Mount Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Features	Adjustable Output, Remote Sense, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)
		Report errors?

MAP110-1005 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAP110-1005 Payment Methods



















MAP110-1005 Shipping Methods













If you have any question about MAP110-1005, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com