



### **MAP110-1012 Information**

Heisener.com

For Reference Only

Manufacture

Part Number MAP110-1012

Manufacturer Bel Power Solutions

Category

Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 12V 80W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MAP110-1012 Specifications**

Manufacturer Part Number         MAP110-1012           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MAP110           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	-	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MAP110           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Manufacturer Part Number	MAP110-1012
Package         -           Series         MAP110           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Manufacturer	Bel Power Solutions
Package         -           Series         MAP110           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         MAP110           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         7.5A           Power (Watts)         90W (120W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         4.242kV (4242V)           Efficiency         80%           Operating Temperature         0°C ~ 70°C (With Derating)           Features         Adjustable Output, Remote Sense, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Series	MAP110
Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)7.5APower (Watts)90W (120W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation4.242kV (4242V)Efficiency80%Operating Temperature0°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Universal InputMounting TypeChassis MountSize / Dimension7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Size / Dimension  12V  12V  12V  12V  12V  12V  12V  12	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  -  Voltage - Output 4  -  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension   Current - Output (Max)	Voltage - Output 1	12V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  80%  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  80%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4.242kV (4242V)  Efficiency  80%  Operating Temperature  O°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation 4.242kV (4242V)  Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Current - Output (Max)	7.5A
Voltage - Isolation  4.242kV (4242V)  Efficiency  80%  Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Power (Watts)	90W (120W Forced Air)
Efficiency 80%  Operating Temperature 0°C ~ 70°C (With Derating)  Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Applications	ITE (Commercial)
Operating Temperature  0°C ~ 70°C (With Derating)  Features  Adjustable Output, Remote Sense, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Voltage - Isolation	4.242kV (4242V)
Features Adjustable Output, Remote Sense, Universal Input  Mounting Type Chassis Mount  Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Efficiency	80%
Mounting Type Chassis Mount  Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Operating Temperature	0°C ~ 70°C (With Derating)
Size / Dimension 7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)	Features	Adjustable Output, Remote Sense, Universal Input
· · ·	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.00" L x 4.30" W x 1.97" H (177.8mm x 109.2mm x 50.0mm)
		Report errors?

#### **MAP110-1012 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **MAP110-1012 Payment Methods**





















## **MAP110-1012 Shipping Methods**













If you have any question about MAP110-1012, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com