

MAX1117EKA-T

MAX1117EKA-T Information

IIII an		MAX1117EKA-T Maxim Integrated Integrated Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC)	
	Description	IC ADC LP 8-BIT SINGLE SOT23-8	
	Package	SOT-23-8	「同う後生い
		For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAX1117EKA-T Specifications

Category Integrate Circuits (ICs) Data Acquisition - Analog to Digital Converters (ADC) Package SOT-23-8 Series		
CategoryIntegrated Circuits (ICs)Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8Series-Number of Bits8Sampling Rate (Per Second)100kNumber of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8Mounting Type-Supplier Device PackageSOT-23-8Mounting Type-	Manufacturer Part Number	MAX1117EKA-T
Data Acquisition - Analog to Digital Converters (ADC)PackageSOT-23-8Series-Number of Bits8Sampling Rate (Per Second)100kNumber of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCNumber of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Peakage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-Architegrapped-	Manufacturer	Maxim Integrated
PackageSOT-23-8Series-Number of Bits8Sampling Rate (Per Second)100kNumber of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Features-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8Mounting Type-Voltagi Type-	Category	Integrated Circuits (ICs)
Series - Number of Bits 8 Sampling Rate (Per Second) 100k Number of Inputs 2 Input Type Single Ended Data Interface SPI Configuration MUX-S/H-ADC Ratio - S/H:ADC 1:1 Number of A/D Converters 1 Architecture SAR Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 3.6 V Voltage - Supply, Digital 2.7 V ~ 3.6 V Operating Temperature - Package / Case SOT - 23.8 Supplier Device Package SOT - 23.8		Data Acquisition - Analog to Digital Converters (ADC)
Number of Bits8Sampling Rate (Per Second)100kNumber of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H: ADC1.1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating Temperature40°C ~ 85°CSupplier Device PackageSOT-23-8Mounting Type-	Package	SOT-23-8
Sampling Rate (Per Second)100kNumber of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Package / CaseSOT - 23.8Supplier Device PackageSOT - 23.8Mounting Type-	Series	-
Number of Inputs2Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VPeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Number of Bits	8
Input TypeSingle EndedData InterfaceSPIConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital-Peatures-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Sampling Rate (Per Second)	100k
Data InterfaceSPIData InterfaceMUX-S/H-ADCConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Number of Inputs	2
ConfigurationMUX-S/H-ADCRatio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital.7 V ~ 3.6 VPeatures-Operating Temperature40°C ~ 85°CPackage / CaseSOT-23-8Munting Type.	Input Type	Single Ended
Ratio - S/H:ADC1:1Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Data Interface	SPI
Number of A/D Converters1ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Configuration	MUX-S/H-ADC
ArchitectureSARReference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device Package-Mounting Type-	Ratio - S/H:ADC	1:1
Reference TypeInternalVoltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Number of A/D Converters	1
Voltage - Supply, Analog2.7 V ~ 3.6 VVoltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Architecture	SAR
Voltage - Supply, Digital2.7 V ~ 3.6 VFeatures-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Reference Type	Internal
Features-Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Voltage - Supply, Analog	2.7 V ~ 3.6 V
Operating Temperature-40°C ~ 85°CPackage / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Voltage - Supply, Digital	2.7 V ~ 3.6 V
Package / CaseSOT-23-8Supplier Device PackageSOT-23-8Mounting Type-	Features	-
Supplier Device PackageSOT-23-8Mounting Type-	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	SOT-23-8
	Supplier Device Package	SOT-23-8
Report errors?	Mounting Type	-
		Report errors?

MAX1117EKA-T Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX1117EKA-T Payment Methods



MAX1117EKA-T Shipping Methods



If you have any question about MAX1117EKA-T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com