



MAX14930FASE+ Information



For Reference Only

Part Number MAX14930FASE+ Manufacturer Maxim Integrated

Category Isolators

Digital Isolators

Description DGTL ISO 2.75KV GEN PURP 16SOIC

Package 16-SOIC (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX14930FASE+ Specifications

Manufacturer Part Number MAX14930FASE+ Manufacturer Maxim Integrated Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Ins Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		
Category Isolators Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Ins Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature 40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer Part Number	MAX14930FASE+
Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Ins Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Manufacturer	Maxim Integrated
Package 16-SOIC (0.154", 3.90mm Width) Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/μs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) 1ns Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Category	Isolators
Series - Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Ins Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC		Digital Isolators
Technology Capacitive Coupling Type General Purpose Isolated Power No Number of Channels 4 Inputs - Side 1/Side 2 4/0 Channel Type Unidirectional Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/µs (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Ins Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Package	16-SOIC (0.154", 3.90mm Width)
TypeGeneral PurposeIsolated PowerNoNumber of Channels4Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation2750VrmsCommon Mode Transient Immunity (Min)25kV/μs (Typ)Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)7.5ns, 7.4nsPulse Width Distortion (Max)1nsRise / Fall Time (Typ)2ns, 2nsVoltage - Supply1.71 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Series	-
Isolated PowerNoNumber of Channels4Inputs - Side 1/Side 2 $4/0$ Channel TypeUnidirectionalVoltage - Isolation $2750Vrms$ Common Mode Transient Immunity (Min) $25kV/\mu s$ (Typ)Data Rate $150Mbps$ Propagation Delay tpLH / tpHL (Max) $7.5ns$, $7.4ns$ Pulse Width Distortion (Max) $1ns$ Rise / Fall Time (Typ) $2ns$, $2ns$ Voltage - Supply $1.71 V \sim 5.5 V$ Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ Package / Case $16-SOIC$ (0.154° , $3.90mm$ Width)Supplier Device Package $16-SOIC$	Technology	Capacitive Coupling
Number of Channels4Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation2750VrmsCommon Mode Transient Immunity (Min)25kV/μs (Typ)Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)7.5ns, 7.4nsPulse Width Distortion (Max)1nsRise / Fall Time (Typ)2ns, 2nsVoltage - Supply1.71 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Туре	General Purpose
Inputs - Side 1/Side 24/0Channel TypeUnidirectionalVoltage - Isolation2750VrmsCommon Mode Transient Immunity (Min)25kV/μs (Typ)Data Rate150MbpsPropagation Delay tpLH / tpHL (Max)7.5ns, 7.4nsPulse Width Distortion (Max)InsRise / Fall Time (Typ)2ns, 2nsVoltage - Supply1.71 V ~ 5.5 VOperating Temperature-40°C ~ 125°CPackage / Case16-SOIC (0.154", 3.90mm Width)Supplier Device Package16-SOIC	Isolated Power	No
Channel Type Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC Unidirectional Unidirectional Unidirectional 2750Vrms 25kV/µs (Typ) 150Mbps 7.5ns, 7.4ns Ins 2ns, 2ns 1ns 1ns 1ns 1ns Voltage - Supply 1.71 V ~ 5.5 V	Number of Channels	4
Voltage - Isolation 2750Vrms Common Mode Transient Immunity (Min) 25kV/ μ s (Typ) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) 1ns Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	4/0
Common Mode Transient Immunity (Min) Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 150Mbps Propagation Delay tpLH / tpHL (Max) 7.5ns, 7.4ns Pulse Width Distortion (Max) 1ns Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	2750Vrms
Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Common Mode Transient Immunity (Min)	25kV/μs (Typ)
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V ~ 5.5 V Operating Temperature -40°C ~ 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package	Data Rate	150Mbps
Rise / Fall Time (Typ) 2ns, 2ns Voltage - Supply 1.71 V \sim 5.5 V Operating Temperature -40°C \sim 125°C Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Propagation Delay tpLH / tpHL (Max)	7.5ns, 7.4ns
Voltage - Supply $1.71 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $16\text{-SOIC} \ (0.154^{\circ}, 3.90 \text{mm Width})$ Supplier Device Package 16-SOIC	Pulse Width Distortion (Max)	1ns
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Rise / Fall Time (Typ)	2ns, 2ns
Package / Case 16-SOIC (0.154", 3.90mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	1.71 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 125°C
	Package / Case	16-SOIC (0.154", 3.90mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

MAX14930FASE+ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX14930FASE+ Payment Methods





















MAX14930FASE+ Shipping Methods













If you have any question about MAX14930FASE+, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com