



MAX14941GWE+ Information



For Reference Only

Part Number MAX14941GWE+ **Manufacturer** Maxim Integrated

Category Isolators

Digital Isolators

Description DGTL ISO 5KV 16SOIC

Package 16-SOIC (0.295", 7.50mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX14941GWE+ Specifications

Manufacturer Part Number MAX14941GWE+ Manufacturer Maxim Integrated Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series - Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC (0.295", 7.50mm Width)		
Category Isolators Package 16-SOIC (0.295", 7.50mm Width) Series - Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Manufacturer Part Number	MAX14941GWE+
Package 16-SOIC (0.295", 7.50mm Width) Series - Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Manufacturer	Maxim Integrated
Package 16-SOIC (0.295", 7.50mm Width) Series - Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/μs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Category	Isolators
Series - Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC		Digital Isolators
Technology Capacitive Coupling Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/μs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Package	16-SOIC (0.295", 7.50mm Width)
Type RS485 Isolated Power No Number of Channels 3 Inputs - Side 1/Side 2 2/1 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Series	-
Isolated Power Number of Channels Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation Common Mode Transient Immunity (Min) Data Rate Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) Voltage - Supply Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC No Unidirectional Volidirectional Volidirectional Volidirectional Sylv/µs (Typ) Unidirectional Souverms 6808 Food No 1500 (Nas) - 1500 (Nas) 1500 (Nas)	Technology	Capacitive Coupling
Number of Channels3Inputs - Side 1/Side 22/1Channel TypeUnidirectionalVoltage - Isolation5000VrmsCommon Mode Transient Immunity (Min)35kV/μs (Typ)Data Rate20MbpsPropagation Delay tpLH / tpHL (Max)68ns, 68nsPulse Width Distortion (Max)-Rise / Fall Time (Typ)15ns, 15ns (Max)Voltage - Supply1.71 V ~ 5.5 V, 4.5 V ~ 5.5 VOperating Temperature-40°C ~ 105°CPackage / Case16-SOIC (0.295", 7.50mm Width)Supplier Device Package16-SOIC	Туре	RS485
Inputs - Side 1/Side 2 Channel Type Unidirectional Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Isolated Power	No
Channel Type Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) Pulse Width Distortion (Max) Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Number of Channels	3
Voltage - Isolation 5000Vrms Common Mode Transient Immunity (Min) 35kV/µs (Typ) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Inputs - Side 1/Side 2	2/1
Common Mode Transient Immunity (Min) Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Channel Type	Unidirectional
Data Rate 20Mbps Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Isolation	5000Vrms
Propagation Delay tpLH / tpHL (Max) 68ns, 68ns Pulse Width Distortion (Max) - Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Common Mode Transient Immunity (Min)	35kV/µs (Typ)
Pulse Width Distortion (Max) Rise / Fall Time (Typ) 15ns, 15ns (Max) Voltage - Supply 1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V Operating Temperature -40°C ~ 105°C Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package	Data Rate	20Mbps
Rise / Fall Time (Typ) $15ns, 15ns \text{ (Max)}$ Voltage - Supply $1.71 \text{ V} \sim 5.5 \text{ V}, 4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC (0.295'', 7.50mm Width)}$ Supplier Device Package 16-SOIC	Propagation Delay tpLH / tpHL (Max)	68ns, 68ns
Voltage - Supply $1.71 \text{ V} \sim 5.5 \text{ V}, 4.5 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case $16\text{-SOIC} (0.295'', 7.50 \text{mm Width})$ Supplier Device Package 16-SOIC	Pulse Width Distortion (Max)	-
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Rise / Fall Time (Typ)	15ns, 15ns (Max)
Package / Case 16-SOIC (0.295", 7.50mm Width) Supplier Device Package 16-SOIC	Voltage - Supply	1.71 V ~ 5.5 V, 4.5 V ~ 5.5 V
Supplier Device Package 16-SOIC	Operating Temperature	-40°C ~ 105°C
	Package / Case	16-SOIC (0.295", 7.50mm Width)
Report errors?	Supplier Device Package	16-SOIC
		Report errors?

MAX14941GWE+ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX14941GWE+ Payment Methods



















MAX14941GWE+ Shipping Methods













If you have any question about MAX14941GWE+, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com