



MAX15012CASA+ Information



Part Number MAX15012CASA+

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)
PMIC - Gate Drivers

DescriptionIC HALF-BRIDGE MOSFET DVR 8-SOIC**Package**8-SOIC (0.154", 3.90mm Width) Exposed Pad

For the pricing/inventory/lead time, please contact

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX15012CASA+ Specifications

Manufacturer Part Number MAX15012CASA+ Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Package 8-SOIC (0.154", 3.90mm Width) Exposed Pad Series - Driven Configuration Half-Bridge Channel Type Independent Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 8 V ~ 12.6 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 175V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP		
CategoryIntegrated Circuits (ICs)PMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply8 V ~ 12.6 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)175VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Manufacturer Part Number	MAX15012CASA+
PackagePMIC - Gate DriversPackage8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply8 V ~ 12.6 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)175VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Manufacturer	Maxim Integrated
Package8-SOIC (0.154", 3.90mm Width) Exposed PadSeries-Driven ConfigurationHalf-BridgeChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply8 V ~ 12.6 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)175VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Category	Integrated Circuits (ICs)
Series-Driven ConfigurationHalf-BridgeChannel TypeIndependentNumber of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply8 V ~ 12.6 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)175VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP		PMIC - Gate Drivers
Driven Configuration Half-Bridge Channel Type Independent Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 8 V ~ 12.6 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 175V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature 4-0°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Package	8-SOIC (0.154", 3.90mm Width) Exposed Pad
Channel Type Independent Number of Drivers 2 Gate Type N-Channel MOSFET Voltage - Supply 8 V ~ 12.6 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) 2A, 2A Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 175V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Series	-
Number of Drivers2Gate TypeN-Channel MOSFETVoltage - Supply8 V ~ 12.6 VLogic Voltage - VIL, VIH-Current - Peak Output (Source, Sink)2A, 2AInput TypeNon-InvertingHigh Side Voltage - Max (Bootstrap)175VRise / Fall Time (Typ)65ns, 65nsOperating Temperature-40°C ~ 150°C (TJ)Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) Exposed PadSupplier Device Package8-SOIC-EP	Driven Configuration	Half-Bridge
Gate Type N-Channel MOSFET Voltage - Supply 8 V ~ 12.6 V Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Channel Type	Independent
Voltage - Supply Logic Voltage - VIL, VIH - Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Number of Drivers	2
Logic Voltage - VIL, VIH Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Gate Type	N-Channel MOSFET
Current - Peak Output (Source, Sink) Input Type Non-Inverting High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package	Voltage - Supply	8 V ~ 12.6 V
Input Type Non-Inverting High Side Voltage - Max (Bootstrap) 175V Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Logic Voltage - VIL, VIH	-
High Side Voltage - Max (Bootstrap) Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Current - Peak Output (Source, Sink)	2A, 2A
Rise / Fall Time (Typ) 65ns, 65ns Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Input Type	Non-Inverting
Operating Temperature -40°C ~ 150°C (TJ) Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	High Side Voltage - Max (Bootstrap)	175V
Mounting Type Surface Mount Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Rise / Fall Time (Typ)	65ns, 65ns
Package / Case 8-SOIC (0.154", 3.90mm Width) Exposed Pad Supplier Device Package 8-SOIC-EP	Operating Temperature	-40°C ~ 150°C (TJ)
Supplier Device Package 8-SOIC-EP	Mounting Type	Surface Mount
	Package / Case	8-SOIC (0.154", 3.90mm Width) Exposed Pad
Report errors?	Supplier Device Package	8-SOIC-EP
		Report errors?

MAX15012CASA+ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX15012CASA+ Payment Methods



















MAX15012CASA+ Shipping Methods













If you have any question about MAX15012CASA+, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com