

MAX3160EAP+

MAX3160EAP+ Information

www.helsener.com	 MAX3160EAP+ Maxim Integrated Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers IC TXRX RS232/RS485/RS422 20SSOP 20-SSOP (0.209", 5.30mm Width) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAX3160EAP+ Specifications

ManufacturerMaxim IntegratedManufacturerIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage20-SSOP (0.209", 5.30mm Width)Package-Package-TypeTransceiverProtocolRS232, RS422, RS485Pauber of Drivers/Receivers2/2Package500mVData Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP		
CategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage20-SSOP (0.209", 5.30mm Width)Series-TransceiverTransceiverProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Manufacturer Part Number	MAX3160EAP+
Interface - Drivers, Receivers, TransceiversPackage20-SSOP (0.209", 5.30mm Width)Series-TransceiverTransceiverPypeTransceiverProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsAutoring TypeSurface MountAutoring TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Manufacturer	Maxim Integrated
Package20-SSOP (0.209", 5.30mm Width)Geries-SypeTransceiverTypeTransceiverProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsJoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Category	Integrated Circuits (ICs)
Series-TypeTransceiverProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsOtage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP		Interface - Drivers, Receivers, Transceivers
TypeTransceiverProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CAounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)	Package	20-SSOP (0.209", 5.30mm Width)
ProtocolRS232, RS422, RS485Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsOltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CAounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)	Series	-
Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis500mVData Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CPounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Туре	Transceiver
DuplexFullReceiver Hysteresis500mVData Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Protocol	RS232, RS422, RS485
Receiver Hysteresis500mVData Rate10MbpsDotage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Number of Drivers/Receivers	2/2
Data Rate10MbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Duplex	Full
Voltage - Supply3 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Receiver Hysteresis	500mV
Deperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Data Rate	10Mbps
Automating TypeSurface MountPackage / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Voltage - Supply	3 V ~ 5.5 V
Package / Case20-SSOP (0.209", 5.30mm Width)Supplier Device Package20-SSOP	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 20-SSOP	Mounting Type	Surface Mount
	Package / Case	20-SSOP (0.209", 5.30mm Width)
Report errors?	Supplier Device Package	20-SSOP
		Report errors?

MAX3160EAP+ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX3160EAP+ Payment Methods



MAX3160EAP+ Shipping Methods



If you have any question about MAX3160EAP+, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com