

MAX3222ECPW

MAX3222ECPW Information

For Reference Only		MAX3222ECPW Texas Instruments Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers IC RS232 3V-5.5V DRVR 20-TSSOP	
	Package	20-TSSOP (0.173", 4.40mm Width) For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAX3222ECPW Specifications

ManufacturerTexas InstrumentsCategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage20-TSSOP (0.173", 4.40mm Width)Package-FypeTransceiverProtocolRS232Number of Drivers/Receivers2/2OuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP		
CategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage20-TSSOP (0.173", 4.40mm Width)Series-FypeTransceiverProtocolRS232Number of Drivers/Receivers2/2DuplexSonowReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VDeperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Manufacturer Part Number	MAX3222ECPW
Interface - Drivers, Receivers, TransceiversPackage20-TSSOP (0.173", 4.40mm Width)Series-TrypeTransceiverProtocolRS232Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Manufacturer	Texas Instruments
Package20-TSSOP (0.173", 4.40mm Width)Series-FypeTransceiverFypeTransceiverProtocolRS232Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Category	Integrated Circuits (ICs)
Series-FypeTransceiverProtocolRS232Number of Drivers/Receivers2/2OuplexFullReceiver Hysteresis300mVOata Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP		Interface - Drivers, Receivers, Transceivers
FypeTransceiverProtocolRS232Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Package	20-TSSOP (0.173", 4.40mm Width)
ProtocolRS232Number of Drivers/Receivers2/2OuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Series	-
Number of Drivers/Receivers2/2DuplexFullReceiver Hysteresis300mVData Rate500kbpsDotage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Туре	Transceiver
DuplexFullReceiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Protocol	RS232
Receiver Hysteresis300mVData Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Number of Drivers/Receivers	2/2
Data Rate500kbpsVoltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Duplex	Full
Voltage - Supply3 V ~ 5.5 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Receiver Hysteresis	300mV
Deperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Data Rate	500kbps
Mounting TypeSurface MountPackage / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Voltage - Supply	3 V ~ 5.5 V
Package / Case20-TSSOP (0.173", 4.40mm Width)Supplier Device Package20-TSSOP	Operating Temperature	0°C ~ 70°C
Supplier Device Package 20-TSSOP	Mounting Type	Surface Mount
	Package / Case	20-TSSOP (0.173", 4.40mm Width)
Report errors?	Supplier Device Package	20-TSSOP
Report chois.		Report errors?

MAX3222ECPW Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX3222ECPW Payment Methods



MAX3222ECPW Shipping Methods



If you have any question about MAX3222ECPW, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com