



MAX4252EUA Information



For Reference Only

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)
Linear - Amplifiers - Ins

Part Number MAX4252EUA

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP GP 3MHZ RRO 8UMAX **Package** 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX4252EUA Specifications

Manufacturer Part NumberMAX4252EUAManufacturerMaxim IntegratedCategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Amplifier TypeGeneral PurposeNumber of Circuits2Output TypePush-Pull, Rail-to-RailSlew Rate0.3 V/μsGain Bandwidth Product3MHz-3db Bandwidth-	
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/µs Gain Bandwidth Product 3MHz	
Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/μs Gain Bandwidth Product 3MHz	
Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/µs Gain Bandwidth Product 3MHz	
Series - Amplifier Type General Purpose Number of Circuits 2 Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/µs Gain Bandwidth Product 3MHz	
Amplifier Type General Purpose Number of Circuits 2 Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/µs Gain Bandwidth Product 3MHz	
Number of Circuits2Output TypePush-Pull, Rail-to-RailSlew Rate $0.3 \text{ V/}\mu\text{s}$ Gain Bandwidth Product 3MHz	
Output Type Push-Pull, Rail-to-Rail Slew Rate 0.3 V/µs Gain Bandwidth Product 3MHz	
Slew Rate 0.3 V/μs Gain Bandwidth Product 3MHz	
Gain Bandwidth Product 3MHz	
2dh Pandwidth	
-3db Bandwidth -	
Current - Input Bias 1pA	
Voltage - Input Offset $70\mu V$	
Current - Supply 420µA	
Current - Output / Channel 68mA	
Voltage - Supply, Single/Dual (\pm) 2.4 V ~ 5.5 V, \pm 1.2 V ~ 2.75 V	
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	
Mounting Type Surface Mount	
Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)	
Supplier Device Package 8-uMAX	
Report 6	errors?

MAX4252EUA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX4252EUA Payment Methods



















MAX4252EUA Shipping Methods













If you have any question about MAX4252EUA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com