



MAX4381EUB+T Information



For Reference Only

Part Number MAX4381EUB+T
Manufacturer Maxim Integrated
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

DescriptionIC OPAMP VFB 210MHZ RRO 10UMAX**Package**10-TFSOP, 10-MSOP (0.118", 3.00mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX4381EUB+T Specifications

Manufacturer Part NumberMAX4381EUB+TManufacturerMaxim IntegratedCategoryIntegrated Circuits (ICs)Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Series-Amplifier TypeVoltage FeedbackNumber of Circuits2Output TypeRail-to-RailSlew Rate485 V/μsGain Bandwidth Product3db Bandwidth210MHzCurrent - Input Bias8.5μAVoltage - Input Offset3mVCurrent - Supply7.5mAVoltage - Supply, Single/Dual (±)4.5 V ~ 11 V, ±2.25 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Supplier Device Package10-uMAX		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 485 V/μs Gain Bandwidth Product - -3db Bandwidth 210MHz Current - Input Bias 8.5μA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Manufacturer Part Number	MAX4381EUB+T
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Series-Amplifier TypeVoltage FeedbackNumber of Circuits2Output TypeRail-to-RailSlew Rate485 V/μsGain Bandwidth Product3db Bandwidth210MHzCurrent - Input Bias8.5μAVoltage - Input Offset3mVCurrent - Supply7.5mACurrent - Output / Channel75mAVoltage - Supply, Single/Dual (±)4.5 V ~ 11 V, ±2.25 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Supplier Device Package10-uMAX	Manufacturer	Maxim Integrated
Package 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 485 V/μs Gain Bandwidth Product - -3db Bandwidth 210MHz Current - Input Bias 8.5μA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Category	Integrated Circuits (ICs)
Series - Amplifier Type Voltage Feedback Number of Circuits 2 Output Type Rail-to-Rail Slew Rate 485 V/μs Gain Bandwidth Product - -3db Bandwidth 210MHz Current - Input Bias 8.5μA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier TypeVoltage FeedbackNumber of Circuits2Output TypeRail-to-RailSlew Rate485 V/μsGain Bandwidth Product3db Bandwidth210MHzCurrent - Input Bias8.5μAVoltage - Input Offset3mVCurrent - Supply7.5mACurrent - Output / Channel75mAVoltage - Supply, Single/Dual (±)4.5 V ~ 11 V, ±2.25 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case10-TFSOP, 10-MSOP (0.118", 3.00mm Width)Supplier Device Package10-uMAX	Package	10-TFSOP, 10-MSOP (0.118", 3.00mm Width)
Number of Circuits2Output TypeRail-to-RailSlew Rate 485 V/μs Gain Bandwidth Product3db Bandwidth 210MHz Current - Input Bias $8.5\mu\text{A}$ Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case 10-TFSOP , 10-MSOP (0.118 ", 3.00mm Width)Supplier Device Package 10-uMAX	Series	-
Output Type Rail-to-Rail Slew Rate 485 V/ μ s Gain Bandwidth Product -3db Bandwidth Current - Input Bias 8.5 μ A Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Amplifier Type	Voltage Feedback
Slew Rate $485 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 210MHz Current - Input Bias $8.5\mu\text{A}$ Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount Package / Case $10\text{-TFSOP}, 10\text{-MSOP} (0.118'', 3.00\text{mm Width})$ Supplier Device Package 10-uMAX	Number of Circuits	2
Gain Bandwidth Product -3db Bandwidth 210MHz Current - Input Bias 8.5μA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature 40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package	Output Type	Rail-to-Rail
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	485 V/μs
Current - Input Bias 8.5µA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Gain Bandwidth Product	-
Voltage - Input Offset $3mV$ Current - Supply $7.5mA$ Current - Output / Channel $75mA$ Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $10\text{-TFSOP}, 10\text{-MSOP} (0.118", 3.00mm \text{ Width})$ Supplier Device Package 10-uMAX	-3db Bandwidth	210MHz
Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Current - Input Bias	8.5μΑ
Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case $10\text{-TFSOP}, 10\text{-MSOP} (0.118", 3.00\text{mm Width})$ Supplier Device Package 10-uMAX	Voltage - Input Offset	3mV
Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Current - Supply	7.5mA
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Current - Output / Channel	75mA
Mounting Type Surface Mount Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Voltage - Supply, Single/Dual (±)	4.5 V ~ 11 V, ±2.25 V ~ 5.5 V
Package / Case 10-TFSOP, 10-MSOP (0.118", 3.00mm Width) Supplier Device Package 10-uMAX	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 10-uMAX	Mounting Type	Surface Mount
	Package / Case	10-TFSOP, 10-MSOP (0.118", 3.00mm Width)
Report errors?	Supplier Device Package	10-uMAX
		Report errors?

MAX4381EUB+T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX4381EUB+T Payment Methods



















MAX4381EUB+T Shipping Methods













If you have any question about MAX4381EUB+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com