



MAX4382EEE+T Information



For Reference Only

Part Number MAX4382EEE+T
Manufacturer Maxim Integrated
Category Integrated Circuits (ICs)

Linear - Amplifiers - Instrumentation, OP Amps,

Buffer Amps

Description IC OPAMP VFB 210MHZ RRO 16QSOP

Package 16-SSOP (0.154", 3.90mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX4382EEE+T Specifications

Manufacturer Part Number MAX4382EEE+T Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 16-SSOP (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 3 Output Type Rail-to-Rail Slew Rate 485 V/μs Gain Bandwidth Product - -3db Bandwidth 210MHz Current - Input Bias 8.5μA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 16-SSOP (0.154", 3.90mm Width)		
Category Integrated Circuits (ICs) Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps Package 16-SSOP (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 3 Output Type Rail-to-Rail Slew Rate 485 V/µs Gain Bandwidth Product -3db Bandwidth 210MHz Current - Input Bias 8.5µA Voltage - Input Offset 3 mV Current - Supply 7.5mA Current - Output / Channel Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature 4.0°C ~ 85°C Mounting Type Surface Mount	Manufacturer Part Number	MAX4382EEE+T
Linear - Amplifiers - Instrumentation, OP Amps, Buffer AmpsPackage16-SSOP (0.154", 3.90mm Width)Series-Amplifier TypeVoltage FeedbackNumber of Circuits3Output TypeRail-to-RailSlew Rate485 V/μsGain Bandwidth Product3db Bandwidth210MHzCurrent - Input Bias8.5μAVoltage - Input Offset3mVCurrent - Supply7.5mACurrent - Output / Channel75mAVoltage - Supply, Single/Dual (±)4.5 V ~ 11 V, ±2.25 V ~ 5.5 VOperating Temperature-40°C ~ 85°CMounting TypeSurface Mount	Manufacturer	Maxim Integrated
Package 16-SSOP (0.154", 3.90mm Width) Series - Amplifier Type Voltage Feedback Number of Circuits 3 Output Type Rail-to-Rail Slew Rate 485 V/µs Gain Bandwidth Product - -3db Bandwidth Product 210MHz Current - Input Bias 8.5µA Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (±) 4.5 V ~ 11 V, ±2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Category	Integrated Circuits (ICs)
Series - Amplifier Type Voltage Feedback Number of Circuits 3 Output Type Rail-to-Rail Slew Rate 485 V/ μ s Gain Bandwidth Product		Linear - Amplifiers - Instrumentation, OP Amps, Buffer Amps
Amplifier Type Number of Circuits Output Type Rail-to-Rail Slew Rate 485 V/μs Gain Bandwidth Product -3db Bandwidth Current - Input Bias Voltage - Input Offset Current - Supply Current - Output / Channel Voltage - Supply, Single/Dual (±) Operating Temperature Mounting Type Voltage - Supply Voltage - Surface Mount	Package	16-SSOP (0.154", 3.90mm Width)
Number of Circuits 3 Output Type Rail-to-Rail Slew Rate 485 V/ μ s Gain Bandwidth Product3db Bandwidth 210MHz Current - Input Bias 8.5 μ A Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Series	-
Output Type Rail-to-Rail Slew Rate $485 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 210MHz Current - Input Bias $8.5\mu\text{A}$ Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Amplifier Type	Voltage Feedback
Slew Rate $485 \text{ V/}\mu\text{s}$ Gain Bandwidth Product3db Bandwidth 210MHz Current - Input Bias $8.5\mu\text{A}$ Voltage - Input Offset 3mV Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Number of Circuits	3
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Output Type	Rail-to-Rail
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Slew Rate	485 V/μs
Current - Input Bias $8.5\mu A$ Voltage - Input Offset $3mV$ Current - Supply $7.5mA$ Current - Output / Channel $75mA$ Voltage - Supply, Single/Dual (\pm) $4.5\ V \sim 11\ V, \pm 2.25\ V \sim 5.5\ V$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount	Gain Bandwidth Product	-
Voltage - Input Offset $3mV$ Current - Supply $7.5mA$ Current - Output / Channel $75mA$ Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	-3db Bandwidth	210MHz
Current - Supply 7.5mA Current - Output / Channel 75mA Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Current - Input Bias	8.5μΑ
Current - Output / Channel $75mA$ Voltage - Supply, Single/Dual (\pm) $4.5 \text{ V} \sim 11 \text{ V}, \pm 2.25 \text{ V} \sim 5.5 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Input Offset	3mV
Voltage - Supply, Single/Dual (\pm) 4.5 V ~ 11 V, \pm 2.25 V ~ 5.5 V Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Current - Supply	7.5mA
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Current - Output / Channel	75mA
Mounting Type Surface Mount	Voltage - Supply, Single/Dual (±)	4.5 V ~ 11 V, ±2.25 V ~ 5.5 V
	Operating Temperature	-40°C ~ 85°C
Package / Case 16-SSOP (0.154", 3.90mm Width)	Mounting Type	Surface Mount
	Package / Case	16-SSOP (0.154", 3.90mm Width)
Supplier Device Package 16-QSOP	Supplier Device Package	16-QSOP
Report error		Report errors?

MAX4382EEE+T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX4382EEE+T Payment Methods





















MAX4382EEE+T Shipping Methods













If you have any question about MAX4382EEE+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com