

# MAX4532CWP+T

#### MAX4532CWP+T Information

| www.belsener.com   | Part Number  | MAX4532CWP+T   |   |
|--------------------|--------------|--|---|
|                    | Manufacturer | Maxim Integrated   |   |
|                    | Category     | Integrated Circuits (ICs)<br>Interface - Analog Switches, Multiplexers,<br>Demultiplexers  | 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 -<br>1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1997 - 1<br>1997 - 199 |
|                    | Description  | IC MULTIPLEXER TRPL 1X2 20SOIC   | H   |
|                    | Package      | 20-SOIC (0.295", 7.50mm Width)   |   |
| For Reference Only |              | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com | Request a Quote   |

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# MAX4532CWP+T Specifications

| Manufacturer Part Number               | MAX4532CWP+T  |  |
|--|---|--|
| Manufacturer                           | Maxim Integrated  |  |
| Category                               | Integrated Circuits (ICs)                                 |  |
|  | Interface - Analog Switches, Multiplexers, Demultiplexers |  |
| Package                                | 20-SOIC (0.295", 7.50mm Width)                            |  |
| Series                                 | -   |  |
| Switch Circuit                         | SPDT  |  |
| Multiplexer/Demultiplexer Circuit      | 2:1   |  |
| Number of Circuits                     | 3   |  |
| On-State Resistance (Max)              | 75 Ohm  |  |
| Channel-to-Channel Matching (Ron)      | 1 Ohm   |  |
| Voltage - Supply, Single (V+)          | 2 V ~ 12 V  |  |
| Voltage - Supply, Dual (V±)            | ±2 V ~ 6 V  |  |
| Switch Time (Ton, Toff) (Max)          | 150ns, 100ns  |  |
| -3db Bandwidth                         | -   |  |
| Charge Injection                       | 1.5pC   |  |
| Channel Capacitance (CS(off), CD(off)) | 3pF, 15pF   |  |
| Current - Leakage (IS(off)) (Max)      | lnA   |  |
| Crosstalk                              | -92dB @ 1MHz  |  |
| Operating Temperature                  | 0°C ~ 70°C (TA)   |  |
| Package / Case                         | 20-SOIC (0.295", 7.50mm Width)                            |  |
| Supplier Device Package                | 20-SO   |  |
|  | Report errors?  |  |

#### MAX4532CWP+T Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MAX4532CWP+T Payment Methods



## MAX4532CWP+T Shipping Methods



If you have any question about MAX4532CWP+T, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com