

MAX483ECSA+

MAX483ECSA+ Information

| Ň | new prisener.com | MAX483ECSA+ Maxim Integrated Integrated Circuits (ICs) Interface - Drivers, Receivers, Transceivers IC TXRX RS485/RS422 LOWPWR 8SOIC 8-SOIC (0.154", 3.90mm Width) For the pricing/inventory/lead time, please contact | |
|----|-------------------|--|-----------------|
| Fo | or Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAX483ECSA+ Specifications

| ManufacturerMaxim IntegratedCategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage8-SOIC (0.154", 3.90mm Width)Series-TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting Type8-SOIC (0.154", 3.90mm Width) | | |
|--|-----------------------------|---|
| CategoryIntegrated Circuits (ICs)Interface - Drivers, Receivers, TransceiversPackage8-SOIC (0.154", 3.90mm Width)Series-TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Manufacturer Part Number | MAX483ECSA+ |
| Interface - Drivers, Receivers, TransceiversPackage8-SOIC (0.154", 3.90mm Width)Series-TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Manufacturer | Maxim Integrated |
| Package8-SOIC (0.154", 3.90mm Width)Series-TypeTransceiverTypeSeriesProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating TemperatureSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Category | Integrated Circuits (ICs) |
| Series-Series-TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | | Interface - Drivers, Receivers, Transceivers |
| TypeTransceiverProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) | Package | 8-SOIC (0.154", 3.90mm Width) |
| ProtocolRS422, RS485Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width) | Series | - |
| Number of Drivers/Receivers1/1DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Туре | Transceiver |
| DuplexHalfReceiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Protocol | RS422, RS485 |
| Receiver Hysteresis70mVData Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Number of Drivers/Receivers | 1/1 |
| Data Rate250kbpsVoltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Duplex | Half |
| Voltage - Supply4.75 V ~ 5.25 VOperating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Receiver Hysteresis | 70mV |
| Operating Temperature0°C ~ 70°CMounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Data Rate | 250kbps |
| Mounting TypeSurface MountPackage / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Voltage - Supply | 4.75 V ~ 5.25 V |
| Package / Case8-SOIC (0.154", 3.90mm Width)Supplier Device Package8-SOIC | Operating Temperature | $0^{\circ}\mathrm{C} \sim 70^{\circ}\mathrm{C}$ |
| Supplier Device Package 8-SOIC | Mounting Type | Surface Mount |
| | Package / Case | 8-SOIC (0.154", 3.90mm Width) |
| Report errors? | Supplier Device Package | 8-SOIC |
| | | Report errors? |

MAX483ECSA+ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX483ECSA+ Payment Methods



MAX483ECSA+ Shipping Methods



If you have any question about MAX483ECSA+, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com