



MAX5102AEUE+T Information



For Reference Only

Part Number MAX5102AEUE+T

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)

Data Acquisition - Digital to Analog Converters

(DAC)

Description IC DAC 8BIT DUAL PAR-IN 16-TSSOP

Package 16-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX5102AEUE+T Specifications

Manufacturer Part NumberMAX5102AEUE+TManufacturerMaxim IntegratedCategoryIntegrated Circuits (ICs)Data Acquisition - Digital to Analog Converters (DAC)Package16-TSSOP (0.173", 4.40mm Width)Series-Number of Bits8Number of D/A Converters2Settling Time6μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 16-TSSOP (0.173", 4.40mm Width) Series Number of Bits Number of D/A Converters 2 Settling Time 6µs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface Reference Type External Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital External Differential (LSB) ±1 (Max), ±1 (Max)
Data Acquisition - Digital to Analog Converters (DAC)Package16-TSSOP (0.173", 4.40mm Width)Series-Number of Bits8Number of D/A Converters2Settling Time6μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)
Package16-TSSOP (0.173", 4.40mm Width)Series-Number of Bits8Number of D/A Converters2Settling Time6μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Number of Bits8Number of D/A Converters2Settling Time $6\mu s$ (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
Number of D/A Converters2Settling Time $6\mu s$ (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
Settling Time $6\mu s$ (Typ) Output Type $Voltage - Buffered$ Differential Output No Data Interface $Parallel$ Reference Type $External$ Voltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
Output Type Voltage - Buffered Differential Output No Data Interface Parallel Reference Type External Voltage - Supply, Analog
Differential OutputNoData InterfaceParallelReference TypeExternalVoltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
$ \begin{array}{llllllllllllllllllllllllllllllllllll$
Reference TypeExternalVoltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
Voltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$
Voltage - Supply, Digital 2.7 V \sim 5.5 V INL/DNL (LSB) ± 1 (Max), ± 1 (Max)
INL/DNL (LSB) ± 1 (Max), ± 1 (Max)
A 1' A
Architecture String DAC
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 16-TSSOP (0.173", 4.40mm Width)
Supplier Device Package 16-TSSOP
Mounting Type -
Report error

MAX5102AEUE+T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX5102AEUE+T Payment Methods



















MAX5102AEUE+T Shipping Methods













If you have any question about MAX5102AEUE+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com