



MAX5362PEUK-T Information

Part Number MAX5362PEUK-T
Manufacturer Maxim Integrated
Category Integrated Circuits (

ategory Integrated Circuits (ICs)
Data Acquisition - Digital to Analog Converters

(DAC)

Description IC DAC LP 6BIT 2-WIRE SOT23-5

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX5362PEUK-T Specifications

Manufacturer Part Number MAX5362PEUK-T Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Package SC-74A, SOT-753 Series - Number of Bits 6 Number of D/A Converters 1 Settling Time 20µs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface 12C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V NIL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -		
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package SC-74A, SOT-753 Series - Number of Bits 6 Number of D/A Converters 1 Settling Time 20μs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Manufacturer Part Number	MAX5362PEUK-T
PackageSC-74A, SOT-753Series-Number of Bits6Number of D/A Converters1Settling Time20μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceI2CReference TypeInternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureCurrent SteeringOperating Temperature-40°C ~ 85°CPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Manufacturer	Maxim Integrated
Package SC-74A, SOT-753 Series - Number of Bits 6 Number of D/A Converters 1 Settling Time 20μs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Category	Integrated Circuits (ICs)
Series - Number of Bits 6 Number of D/A Converters 1 Settling Time 20μs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface 12C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -		Data Acquisition - Digital to Analog Converters (DAC)
Number of Bits6Number of D/A Converters1Settling Time20μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceI2CReference TypeInternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureCurrent SteeringOperating Temperature-40°C ~ 85°CPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Package	SC-74A, SOT-753
Number of D/A Converters1Settling Time20μs (Typ)Output TypeVoltage - BufferedDifferential OutputNoData InterfaceI2CReference TypeInternalVoltage - Supply, Analog2.7 V ~ 5.5 VVoltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureCurrent SteeringOperating Temperature-40°C ~ 85°CPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Series	-
Settling Time 20µs (Typ) Output Type Voltage - Buffered Differential Output No Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Number of Bits	6
Output Type Differential Output No Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital INL/DNL (LSB) Architecture Operating Temperature Package / Case SC-74A, SOT-753 Supplier Device Package Mounting Type Voltage - Buffered No No Ottage - Buffered I2C Internal 2.7 V ~ 5.5 V Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V Supply -	Number of D/A Converters	1
Differential Output Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) 41 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package Mounting Type - No Internal 2.7 V ~ 5.5 V (Max) - Current Steering SUP-23-5	Settling Time	20μs (Typ)
Data Interface I2C Reference Type Internal Voltage - Supply, Analog 2.7 V ~ 5.5 V Voltage - Supply, Digital 2.7 V ~ 5.5 V INL/DNL (LSB) ±1 (Max), ±1 (Max) Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Output Type	Voltage - Buffered
Reference TypeInternalVoltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}$, $\pm 1 \text{ (Max)}$ ArchitectureCurrent SteeringOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Differential Output	No
Voltage - Supply, Analog $2.7 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.7 \text{ V} \sim 5.5 \text{ V}$ INL/DNL (LSB) $\pm 1 \text{ (Max)}, \pm 1 \text{ (Max)}$ ArchitectureCurrent SteeringOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Package / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Data Interface	I2C
Voltage - Supply, Digital2.7 V ~ 5.5 VINL/DNL (LSB)±1 (Max), ±1 (Max)ArchitectureCurrent SteeringOperating Temperature-40°C ~ 85°CPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5Mounting Type-	Reference Type	Internal
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Voltage - Supply, Analog	2.7 V ~ 5.5 V
Architecture Current Steering Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Voltage - Supply, Digital	2.7 V ~ 5.5 V
Operating Temperature -40°C ~ 85°C Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	INL/DNL (LSB)	± 1 (Max), ± 1 (Max)
Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 Mounting Type -	Architecture	Current Steering
Supplier Device Package SOT-23-5 Mounting Type -	Operating Temperature	-40°C ~ 85°C
Mounting Type -	Package / Case	SC-74A, SOT-753
	Supplier Device Package	SOT-23-5
Report errors?	Mounting Type	-
		Report errors?

MAX5362PEUK-T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX5362PEUK-T Payment Methods





















MAX5362PEUK-T Shipping Methods













If you have any question about MAX5362PEUK-T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com