



MAX548AEUA+ Information



For Reference Only

Part Number MAX548AEUA+
Manufacturer Maxim Integrated
Category Integrated Circuits (ICs)

Data Acquisition - Digital to Analog Converters

(DAC)

Description IC DAC 8BIT DUAL ASYNCH 8-UMAX **Package** 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX548AEUA+ Specifications

Manufacturer Part Number Maxim Integrated Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Number of Bits Number of D/A Converters 2 Settling Time 4µs (Typ) Output Type Output Type Voltage - Unbuffered Differential Output No Data Interface SPI Reference Type Voltage - Supply, Analog Voltage - Supply, Analog Voltage - Supply, Digital 2.5 V ~ 5.5 V INL/DNL (LSB) - **MAX548AEUA+ Maxim Integrated Maxim Integrated Maxim Integrated Integrated Circuits (ICs) **Maxim Integrated **Maxim Integrated **Maxim Integrated **Maxim Integrated **Maxim Integrated **Integrated Circuits (ICs) **Maxim Integrated **Maxim Integrated **Integrated **Converters (DAC) **Maxim Integrated **Maxim Integrated Circuits (ICs) **Maxim Integrated
Category Integrated Circuits (ICs) Data Acquisition - Digital to Analog Converters (DAC) Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Number of Bits Number of D/A Converters 2 Settling Time 4µs (Typ) Output Type Voltage - Unbuffered Differential Output No Data Interface Reference Type Voltage - Supply, Analog Voltage - Supply, Digital 2.5 V ~ 5.5 V
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Number of Bits 8 Number of D/A Converters 2 Settling Time $4\mu s$ (Typ) Output Type Voltage - Unbuffered Differential Output No Data Interface SPI Reference Type Supply Voltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital
Series-Number of Bits8Number of D/A Converters2Settling Time4μs (Typ)Output TypeVoltage - UnbufferedDifferential OutputNoData InterfaceSPIReference TypeSupplyVoltage - Supply, Analog2.5 V ~ 5.5 VVoltage - Supply, Digital2.5 V ~ 5.5 V
Number of Bits8Number of D/A Converters2Settling Time $4\mu s$ (Typ)Output TypeVoltage - UnbufferedDifferential OutputNoData InterfaceSPIReference TypeSupplyVoltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
$\begin{array}{llllllllllllllllllllllllllllllllllll$
Settling Time $4\mu s$ (Typ) Output Type $Voltage$ - Unbuffered Differential Output No Data Interface SPI Reference Type $Supply$ Voltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
Output Type Voltage - Unbuffered Differential Output No Data Interface SPI Reference Type Supply Voltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
$\begin{array}{ccc} \text{Differential Output} & \text{No} \\ \\ \text{Data Interface} & \text{SPI} \\ \\ \text{Reference Type} & \text{Supply} \\ \\ \text{Voltage - Supply, Analog} & 2.5 \text{ V} \sim 5.5 \text{ V} \\ \\ \text{Voltage - Supply, Digital} & 2.5 \text{ V} \sim 5.5 \text{ V} \\ \end{array}$
Data InterfaceSPIReference TypeSupplyVoltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
Reference Type Supply Voltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
Voltage - Supply, Analog $2.5 \text{ V} \sim 5.5 \text{ V}$ Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
Voltage - Supply, Digital $2.5 \text{ V} \sim 5.5 \text{ V}$
INI /DNI (LSB) +0.0 (May)
111L/DITL (LSD) -, EU.7 (IVIdA)
Architecture R-2R
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
Supplier Device Package 8-uMAX
Mounting Type -
Report error

MAX548AEUA+ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX548AEUA+ Payment Methods





















MAX548AEUA+ Shipping Methods













If you have any question about MAX548AEUA+, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com