



MAX6037CAUK25+T Information



For Reference Only

Part Number MAX6037CAUK25+T

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

Description IC VREF SERIES 2.5V SOT23-5

Package SC-74A, SOT-753

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX6037CAUK25+T Specifications

| Manufacturer Part Number MAX6037CAUK25+T Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 2.5 V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50pm/°C Noise - 0.1Hz to 10Hz 14μVp-p Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature 40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | | |
|--|------------------------------|---------------------------|
| Category Integrated Circuits (ICs) PMIC - Voltage Reference Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 2.5V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 14µVp-p Noise - 10Hz to 10kHz 30µVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275µA Current - Cathode - Operating Temperature 40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Manufacturer Part Number | MAX6037CAUK25+T |
| Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 2.5V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 14μVp-p Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Manufacturer | Maxim Integrated |
| Package SC-74A, SOT-753 Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 2.5V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 14μVp-p Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Category | Integrated Circuits (ICs) |
| Series - Reference Type Series Output Type Fixed Voltage - Output (Min/Fixed) 2.5V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 14μVp-p Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | | PMIC - Voltage Reference |
| Reference TypeSeriesOutput TypeFixedVoltage - Output (Min/Fixed)2.5 VVoltage - Output (Max)-Current - Output5mATolerance±0.5%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz14μVp-pNoise - 10Hz to 10kHz30μVrmsVoltage - Input2.7 V ~ 5.5 VCurrent - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5 | Package | SC-74A, SOT-753 |
| Output Type Fixed Voltage - Output (Min/Fixed) 2.5 V Voltage - Output (Max) - Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz 14μVp-p Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Series | - |
| Voltage - Output (Min/Fixed)2.5VVoltage - Output (Max)-Current - Output5mATolerance±0.5%Temperature Coefficient50ppm/°CNoise - 0.1Hz to 10Hz14μVp-pNoise - 10Hz to 10kHz30μVrmsVoltage - Input2.7 V ~ 5.5 VCurrent - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5 | Reference Type | Series |
| Voltage - Output (Max) Current - Output 5mA Tolerance ±0.5% Temperature Coefficient 50ppm/°C Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz 30μVrms Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature 40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package | Output Type | Fixed |
| Current - Output $5mA$ Tolerance $\pm 0.5\%$ Temperature Coefficient $50ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $14\mu Vp-p$ Noise - $10Hz$ to $10kHz$ $30\mu Vrms$ Voltage - Input $2.7 \text{ V} \sim 5.5 \text{ V}$ Current - Supply $275\mu A$ Current - Cathode-Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5 | Voltage - Output (Min/Fixed) | 2.5V |
| Tolerance $\pm 0.5\%$ Temperature Coefficient $50pm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $14\mu Vp-p$ Noise - $10Hz$ to $10kHz$ $30\mu Vrms$ Voltage - Input $2.7 \text{ V} \sim 5.5 \text{ V}$ Current - Supply $275\mu A$ Current - Cathode - $200 \times 100 $ | Voltage - Output (Max) | - |
| Temperature Coefficient $50ppm/^{\circ}C$ Noise - $0.1Hz$ to $10Hz$ $14\mu Vp-p$ Noise - $10Hz$ to $10kHz$ $30\mu Vrms$ Voltage - Input $2.7 V \sim 5.5 V$ Current - Supply $275\mu A$ Current - Cathode - Operating Temperature $-40^{\circ}C \sim 125^{\circ}C$ (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Current - Output | 5mA |
| Noise - 0.1Hz to 10Hz $14\mu V p-p$ Noise - 10Hz to 10kHz $30\mu V rms$ $Voltage - Input$ $2.7 V \sim 5.5 V$ $Current - Supply$ $275\mu A$ $Current - Cathode - Operating Temperature -40^{\circ}C \sim 125^{\circ}C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5$ | Tolerance | ±0.5% |
| Noise - 10Hz to 10kHz Voltage - Input 2.7 V ~ 5.5 V Current - Supply 275μA Current - Cathode - Operating Temperature Ao°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package | Temperature Coefficient | 50ppm/°C |
| Voltage - Input $ 2.7 \text{ V} \sim 5.5 \text{ V} $ $ \text{Current - Supply } 275 \mu \text{A} $ $ \text{Current - Cathode } - $ $ \text{Operating Temperature } -40^{\circ}\text{C} \sim 125^{\circ}\text{C (TA)} $ $ \text{Mounting Type } \text{Surface Mount } $ $ \text{Package / Case } \text{SC-74A, SOT-753} $ $ \text{Supplier Device Package } $ $ \text{SOT-23-5} $ | Noise - 0.1Hz to 10Hz | 14μVp-p |
| Current - Supply275μACurrent - Cathode-Operating Temperature-40°C ~ 125°C (TA)Mounting TypeSurface MountPackage / CaseSC-74A, SOT-753Supplier Device PackageSOT-23-5 | Noise - 10Hz to 10kHz | 30μVrms |
| Current - Cathode - Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Voltage - Input | 2.7 V ~ 5.5 V |
| Operating Temperature -40°C ~ 125°C (TA) Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Current - Supply | 275μΑ |
| Mounting Type Surface Mount Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Current - Cathode | - |
| Package / Case SC-74A, SOT-753 Supplier Device Package SOT-23-5 | Operating Temperature | -40°C ~ 125°C (TA) |
| Supplier Device Package SOT-23-5 | Mounting Type | Surface Mount |
| | Package / Case | SC-74A, SOT-753 |
| Report errors? | Supplier Device Package | SOT-23-5 |
| | | Report errors? |

MAX6037CAUK25+T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX6037CAUK25+T Payment Methods


































If you have any question about MAX6037CAUK25+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com