



MAX6126BASA33+ Information

Manufactur
Category
Heisener com
Description

Part Number MAX6126BASA33+

Manufacturer Maxim Integrated

Category Integrated Circuits (ICs)
PMIC - Voltage Reference

INTEGRATED CIRCUIT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX6126BASA33+ Specifications

Manufacturer Part Number MAX6126BASA33+ Manufacturer Maxim Integrated Category Integrated Circuits (ICs) PMIC - Voltage Reference Package - Series * Reference Type - Output Type - Voltage - Output (Min/Fixed) - Voltage - Output (Max) - Current - Output - Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 0.1Hz to 10Hz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package - Report errors?		
Category Integrated Circuits (ICs) PACKAGE PMIC - Voltage Reference Series * Reference Type - Output Type - Voltage - Output (Min/Fixed) - Voltage - Output (Max) - Current - Output - Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	MAX6126BASA33+
Package - Series * Reference Type - Output Type - Voltage - Output (Min/Fixed) - Voltage - Output (Max) - Current - Output - Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package -	Manufacturer	Maxim Integrated
Package - Series * Reference Type - Output Type - Voltage - Output (Min/Fixed) - Voltage - Output (Max) - Current - Output - Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
Series * Reference Type - Output Type - Voltage - Output (Min/Fixed) - Voltage - Output (Max) - Current - Output - Tolerance - Temperature Coefficient - Noise - 0.1Hz to 10Hz - Noise - 10Hz to 10kHz - Voltage - Input - Current - Supply - Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package -		PMIC - Voltage Reference
Reference Type - Cutput Type - Cutput (Min/Fixed) - Cutput (Min/Fixed) - Cutput (Max) - Cutrent - Output - Outp	Package	-
Output Type-Voltage - Output (Min/Fixed)-Voltage - Output (Max)-Current - Output-Tolerance-Temperature Coefficient-Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode-Operating Temperature-Mounting Type-Package / Case-Supplier Device Package-	Series	*
Voltage - Output (Min/Fixed)-Voltage - Output (Max)-Current - Output-Tolerance-Temperature Coefficient-Noise - 0.1Hz to 10Hz-Noise - 10Hz to 10kHz-Voltage - Input-Current - Supply-Current - Cathode-Operating Temperature-Mounting Type-Package / Case-Supplier Device Package-	Reference Type	-
Voltage - Output (Max) Current - Output Tolerance - Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode Operating Temperature Mounting Type Package / Case Supplier Device Package	Output Type	-
Current - Output - Output - Current - Output - Current - Output - Current - Coefficient - Current - Supply - Current - Cathode - Current - Cathode - Current - Cathode - Current - Cathode - Current	Voltage - Output (Min/Fixed)	-
Tolerance - Coefficient - Coefficient - Course - O.1Hz to 10Hz - Course - Input - Course - Input - Current - Supply - Current - Cathode - Current	Voltage - Output (Max)	-
Temperature Coefficient Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz Voltage - Input Current - Supply Current - Cathode Operating Temperature Mounting Type Package / Case Supplier Device Package - - - - - - - - - - - - -	Current - Output	-
Noise - 0.1Hz to 10Hz Noise - 10Hz to 10kHz - Current - Supply Current - Cathode Operating Temperature Mounting Type August - Case Supplier Device Package - Current - Cathode - Current - Curren	Tolerance	-
Noise - 10Hz to 10kHz - 10Hz to 10hz 10hz	Temperature Coefficient	-
Voltage - Input - Current - Supply - Current - Cathode - Current -	Noise - 0.1Hz to 10Hz	-
Current - Supply - Current - Cathode Operating Temperature Mounting Type Package / Case Supplier Device Package	Noise - 10Hz to 10kHz	-
Current - Cathode - Operating Temperature - Mounting Type - Package / Case - Supplier Device Package -	Voltage - Input	-
Operating Temperature	Current - Supply	-
Mounting Type - Package / Case - Supplier Device Package	Current - Cathode	-
Package / Case - Supplier Device Package -	Operating Temperature	-
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

MAX6126BASA33+ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX6126BASA33+ Payment Methods



















MAX6126BASA33+ Shipping Methods













If you have any question about MAX6126BASA33+, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com