

MAX6686AU40H+

MAX6686AU40H+ Information



Part Number	MAX6686AU40H+
Manufacturer	Maxim Integrated
Category	Sensors, Transducers Temperature Switches
Description	IC SW TEMP DUAL OUT 8-UMAX
Package	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAX6686AU40H+ Specifications

Manufacturer Part NumberMAX6686AU40H+ManufacturerMaxim IntegratedCategorySensors, TransducersTemperature SwitchesTemperature SwitchesPackage-Series-Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Output TypeOpen DrainOutput FunctionActive LowSelectable HysteresisNoSelectable HysteresisSelectable Trip PointYoltage - Supply30µAOurput - Supply20µA
CategorySensors, TransducersTemperature SwitchesPackage8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Temperature SwitchesPackage8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutput TypeOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3V ~ 5.5 VCurrent - Supply200µA
Package8-TSSOP, 8-MSOP (0.118", 3.00mm Width)Series-Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)OmAOutput TypeOpen DrainOutput TypeOverTemp, /OverTempOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply20μA
Series-Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutput TypeOpen DrainOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200μA
Trip Temperature ThresholdHotSwitching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutput TypeActive LowOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3V ~ 5.5 VCurrent - Supply200μA
Switching Temperature40°C ~ 80°C, 125°CAccuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutput functionActive LowOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply20µA
Accuracy±1.5%Current - Output (Max)20mAOutput TypeOpen DrainOutputActive LowOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200μA
Current - Output (Max)20mAOutput TypeOpen DrainOutputActive LowOutput FunctionOverTemp,/OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Output TypeOpen DrainOutputActive LowOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
OutputActive LowOutput FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Output FunctionOverTemp, /OverTempSelectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Selectable HysteresisNoFeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
FeaturesSelectable Trip PointVoltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Voltage - Supply3 V ~ 5.5 VCurrent - Supply200µA
Current - Supply 200µA
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Mounting Type Surface Mount
Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
Supplier Device Package 8-uMAX
Report err

MAX6686AU40H+ Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX6686AU40H+ Payment Methods



MAX6686AU40H+ Shipping Methods



If you have any question about MAX6686AU40H+, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com