



MAX8535AEUA+T Information



For Reference Only

Part Number MAX8535AEUA+T
Manufacturer Maxim Integrated
Category Integrated Circuits (ICs)

PMIC - OR Controllers, Ideal Diodes

Description IC OR CTRLR N+1 8UMAX

Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAX8535AEUA+T Specifications

Manufacturer Part Number MAX8535AEUA+T Manufacturer Maxim Integrated Category Integrated Circuits (ICs) Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Type N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX		
Category Integrated Circuits (ICs) PMIC - OR Controllers, Ideal Diodes Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Type N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Manufacturer Part Number	MAX8535AEUA+T
Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Type N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Manufacturer	Maxim Integrated
Package 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Series - Type N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-UMAX	Category	Integrated Circuits (ICs)
Series - N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX		PMIC - OR Controllers, Ideal Diodes
Type N+1 ORing Controller FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Package	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
FET Type N-Channel Ratio - Input:Output N:1 Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-UMAX	Series	-
Ratio - Input:Output Internal Switch(s) No Delay Time - ON - Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Туре	N+1 ORing Controller
Internal Switch(s) Delay Time - ON Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	FET Type	N-Channel
Delay Time - ON Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Ratio - Input:Output	N:1
Delay Time - OFF 200ns Current - Output (Max) - Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Internal Switch(s)	No
Current - Output (Max) Current - Supply 2mA Voltage - Supply 8 V ~ 14 V Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package	Delay Time - ON	-
Current - Supply $2mA$ Voltage - Supply $8 \text{ V} \sim 14 \text{ V}$ ApplicationsRedundant Power Supplies, Telecom InfrastructureOperating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface MountPackage / Case 8-TSSOP , 8-MSOP (0.118", 3.00mm Width)Supplier Device Package 8-uMAX	Delay Time - OFF	200ns
Voltage - Supply Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Current - Output (Max)	-
Applications Redundant Power Supplies, Telecom Infrastructure Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Current - Supply	2mA
Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Voltage - Supply	8 V ~ 14 V
Mounting Type Surface Mount Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Applications	Redundant Power Supplies, Telecom Infrastructure
Package / Case 8-TSSOP, 8-MSOP (0.118", 3.00mm Width) Supplier Device Package 8-uMAX	Operating Temperature	-40°C ~ 85°C
Supplier Device Package 8-uMAX	Mounting Type	Surface Mount
	Package / Case	8-TSSOP, 8-MSOP (0.118", 3.00mm Width)
Report errors?	Supplier Device Package	8-uMAX
		Report errors?

MAX8535AEUA+T Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAX8535AEUA+T Payment Methods



















MAX8535AEUA+T Shipping Methods













If you have any question about MAX8535AEUA+T, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com