

MB3045S-E3/4W

MB3045S-E3/4W Information

www.hegsener.com	 MB3045S-E3/4W Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE SCHOTTKY 45V 30A TO263AB TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MB3045S-E3/4W Specifications

Manufacturer Part NumberMB3045S-E3/4WManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)30AVoltage - Forward (Vf) (Max) @ If-SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263.3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263.3, D2Pak (2 Leads + Tab), TO-263.4BSupplier Device PackageTO-263.4BSupplier Device PackageSove - 150°C		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)30AVoltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABOperating Temperature - Junction65°C ~ 150°C	Manufacturer Part Number	MB3045S-E3/4W
IndexDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Jo)30AVoltage - Forward (Vf) (Max) @ If70mV @ 30ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200 μ A @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)30AVoltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Category	Discrete Semiconductor Products
Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Jo)30AVoltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery $=< 500$ ms, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200 μ A @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Jo)30AVoltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery =< 500ns, > 200mA (Jo)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, FSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-50°C ~ 150°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Voltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io)30AVoltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200 μ A @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Series	-
Current - Average Rectified (Io) $30A$ Voltage - Forward (Vf) (Max) @ If $700mV @ 30A$ SpeedFast Recovery $= 500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $200\muA @ 45V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction $-65^\circC ~ 150^\circC$	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If700mV @ 30ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $200\muA @ 45V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction $-65^{\circ}C \sim 150^{\circ}C$	Voltage - DC Reverse (Vr) (Max)	45V
SpeedFast Recovery $=< 500$ ns, > 200 mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr 200μ A @ $45V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Current - Average Rectified (Io)	30A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Voltage - Forward (Vf) (Max) @ If	700mV @ 30A
Current - Reverse Leakage @ Vr200µA @ 45VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Current - Reverse Leakage @ Vr	200µA @ 45V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Capacitance @ Vr, F	-
Supplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 150°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 150^{\circ}\text{C}$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	TO-263AB
Report errors?	Operating Temperature - Junction	-65°C ~ 150°C
		Report errors?

MB3045S-E3/4W Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MB3045S-E3/4W Payment Methods



MB3045S-E3/4W Shipping Methods



If you have any question about MB3045S-E3/4W, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com