

Heisener.com

MB95F128MBPMC-G-N9-YE1

MB95F128MBPMC-G-N9-YE1 Information

Part Number MB95F128MBPMC-G-N9-YE1
Manufacturer Cypress Semiconductor Corp
Category Integrated Circuits (ICs)
Embedded - Microcontrollers

Description IC MCU 8BIT 60KB FLASH 100LQFP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MB95F128MBPMC-G-N9-YE1 Specifications

Manufacturer Part Number MB95F128MBPMC-G-N9-YEI Manufacturer Cypress Semiconductor Corp Category Integrated Circuits (ICs) Embedded - Microcontrollers Package - Series F2MC MB95120MB Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity I2C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package - Report errors?		
Category Integrated Circuits (ICs) Embedded - Microcontrollers Package - Series F2MC MB95120MB Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity I2C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Manufacturer Part Number	MB95F128MBPMC-G-N9-YE1
Package - Series F2MC MB95120MB Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity 12C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Manufacturer	Cypress Semiconductor Corp
Package - Series F2MC MB95120MB Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity I2C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Category	Integrated Circuits (ICs)
Series F2MC MB95120MB Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity 12C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -		Embedded - Microcontrollers
Core Processor F2MC-8FX Core Size 8-Bit Speed 16MHz Connectivity 12C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Package	-
Core Size 8-Bit Speed 16MHz Connectivity 12C, LIN, SIO, UART/USART Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Series	F2MC MB95120MB
Speed16MHzConnectivity12C, LIN, SIO, UART/USARTPeripheralsLCD, LVD, POR, PWM, WDTNumber of I/O87Program Memory Size60KB (60K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size2K x 8Voltage - Supply (Vcc/Vdd)2.4 V ~ 5.5 VData ConvertersA/D 12x8/10bOscillator TypeExternalOperating Temperature-40°C ~ 105°CMounting Type-Package / Case-Supplier Device Package-	Core Processor	F2MC-8FX
Connectivity Peripherals LCD, LVD, POR, PWM, WDT Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - RAM Size Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature A-0°C ~ 105°C Mounting Type Package / Case Supplier Device Package - Supplier Device Package I LCD, LVD, POR, PWM, WDT 87 87 87 87 87 87 87 87 88 89 60KB (60K x 8) FLASH 60KB (60K x 8) 87 87 88 60KB (60K x 8) 87 87 88 60KB (60K x 8) 87 88 60KB (60K x 8) 89 60KB (60K x 8) 60KB (60K x 8) 87 60KB (60K x 8) 60KB (60K x 8) 87 60KB (60K x 8) 60KB (60K x 8) 60KB (60K x 8) 60KB (60K x 8) 87 60KB (60K x 8) 60KB (60KB x 8) 60KB (Core Size	8-Bit
Peripherals Number of I/O 87 Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b External Operating Temperature Mounting Type -40°C ~ 105°C Mounting Type -2 Supplier Device Package -3 LCD, LVD, POR, PWM, WDT 87 87 87 87 87 88 88 88 88 60KB (60K x 8) FLASH - EXSUPPLICATION FLASH - 88 60KB (60K x 8) FLASH 60KB (60K x 8) 60KB (60K x 8) FLASH 60KB (60K x 8) 60KB (60K x 8) FLASH 60KB (60K x 8) 60KB	Speed	16MHz
Number of I/O87Program Memory Size60KB (60K x 8)Program Memory TypeFLASHEEPROM Size-RAM Size2K x 8Voltage - Supply (Vcc/Vdd)2.4 V ~ 5.5 VData ConvertersA/D 12x8/10bOscillator TypeExternalOperating Temperature-40°C ~ 105°CMounting Type-Package / Case-Supplier Device Package-	Connectivity	I2C, LIN, SIO, UART/USART
Program Memory Size 60KB (60K x 8) Program Memory Type FLASH EEPROM Size - 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Peripherals	LCD, LVD, POR, PWM, WDT
Program Memory Type FLASH EEPROM Size - RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Number of I/O	87
EEPROM Size - 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type Package / Case - Supplier Device Package	Program Memory Size	60KB (60K x 8)
RAM Size 2K x 8 Voltage - Supply (Vcc/Vdd) 2.4 V ~ 5.5 V Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Program Memory Type	FLASH
Voltage - Supply (Vcc/Vdd)2.4 V ~ 5.5 VData ConvertersA/D 12x8/10bOscillator TypeExternalOperating Temperature-40°C ~ 105°CMounting Type-Package / Case-Supplier Device Package-	EEPROM Size	-
Data Converters A/D 12x8/10b Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package	RAM Size	2K x 8
Oscillator Type External Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Voltage - Supply (Vcc/Vdd)	2.4 V ~ 5.5 V
Operating Temperature -40°C ~ 105°C Mounting Type - Package / Case - Supplier Device Package -	Data Converters	A/D 12x8/10b
Mounting Type - Package / Case - Supplier Device Package	Oscillator Type	External
Package / Case - Supplier Device Package -	Operating Temperature	-40°C ~ 105°C
Supplier Device Package -	Mounting Type	-
	Package / Case	-
Report errors?	Supplier Device Package	-
		Report errors?

MB95F128MBPMC-G-N9-YE1 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MB95F128MBPMC-G-N9-YE1 Payment Methods





















MB95F128MBPMC-G-N9-YE1 Shipping Methods













If you have any question about MB95F128MBPMC-G-N9-YE1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com