

MBC180-1048L

ote

MBC180-1048L Information

rielsener ser	 MBC180-1048L Bel Power Solutions Power Supplies - External/Internal (Off-Board) AC DC Converters AC/DC CONVERTER 48V 120/180W - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quo

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBC180-1048L Specifications

Manufacturer Part NumberMBC180-1048LManufacturerBel Power SolutionsCategoryPower Supplies - External/Internal (Off-Board)ACDC ConvertersACDC ConvertersPackage-SeriesMBC180TypeOpen FrameNumber of Outputs1Voltage - Input85 - 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 8-Voltage - Output 9-Voltage - Output 9-Voltage - Output 9-Voltage - Output 4-Voltage - Output 4-Voltage - Output 5-Voltage - Output 4-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7- <th>•</th> <th></th> <th></th>	•			
CategoryPower Supplies - External/Internal (Off-Board)AC DC ConvertersPackage-SeriesMBC180TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-<	Manufacturer Part Number	MBC180-1048L		
AC DC ConvertersPackage-SeriesMBC180TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - SolationHedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00°L x 2.00°W x 0.75° H (101.6mm x 50.8mm x 19.1mm)	Manufacturer	Bel Power Solutions		
Package.SeriesMBC180TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2.Voltage - Output 3.Voltage - Output 4.Voltage - Output 5.Voltage - Output 6.Voltage - Output 7.Voltage - Solation.Voltage - Isolation.Voltage - Isolation.Voltage - Solation.Voltage - Solation	Category	Power Supplies - External/Internal (Off-Board)		
SeriesMBC180TypeOpen FrameNumber of Outputs1Voltage of Outputs85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 4-Voltage - Output 42.5APower (Watts)120W (180W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating TemperatureAjustabe Output, DC Input Capable, PFC, Standby Output, Universal InputFeaturesChasis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)		AC DC Converters		
TypeOpen FrameNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Voltage - Output 5-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Output 7-Voltage - Output 6-Voltage - Output 7-Voltage - Output 7-Voltage - Output 7-Voltage - Solation-Voltage - Isolation-Voltage - Isolation-Voltage - Solation-Voltage - Solation-	Package	-		
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 5 2.5A Power (Wats) 120W (180W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Series	MBC180		
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W (180W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input Mounting Type 6Aosis Mount Size / Dimension 4.00° L x 2.00° W x 0.75° H (101.6mm x 50.8mm x 19.1mm)	Туре	Open Frame		
Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W (180W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Number of Outputs	1		
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W (180W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Input	85 ~ 264 VAC		
Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 2.5A Power (Watts) 120W (180W Forced Air) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -40°C ~ 70°C (With Derating) Features Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Output 1	48V		
Voltage - Output 4-Current - Output (Max)2.5APower (Watts)120W (180W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Output 2	-		
Current - Output (Max)2.5APower (Watts)120W (180W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Output 3	-		
Power (Watts)120W (180W Forced Air)ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Output 4	-		
ApplicationsMedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Current - Output (Max)	2.5A		
InAnd the second se	Power (Watts)	120W (180W Forced Air)		
Efficiency92%Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Applications	Medical		
Operating Temperature-40°C ~ 70°C (With Derating)FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Voltage - Isolation	4kV (4000V)		
FeaturesAdjustable Output, DC Input Capable, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Efficiency	92%		
Mounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Operating Temperature	$-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)		
Size / Dimension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)	Features	Adjustable Output, DC Input Capable, PFC, Standby Output, Universal Input		
	Mounting Type	Chassis Mount		
Report errors?	Size / Dimension	mension 4.00" L x 2.00" W x 0.75" H (101.6mm x 50.8mm x 19.1mm)		
			Report errors?	

MBC180-1048L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBC180-1048L Payment Methods



MBC180-1048L Shipping Methods



If you have any question about MBC180-1048L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com