



### **MBC201-1012G Information**



For Reference Only

**Part Number** MBC201-1012G **Manufacturer** Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 12V 160/200W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MBC201-1012G Specifications**

Manufacturer Part Number         MBC201-1012G           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MBC201           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MBC201           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Manufacturer Part Number	MBC201-1012G
Package         -           Series         MBC201           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Manufacturer	Bel Power Solutions
Package         -           Series         MBC201           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         MBC201           Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Package	-
Number of Outputs         1           Voltage - Input         90 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         13.33A           Power (Watts)         160W (200W Forced Air)           Applications         Medical           Voltage - Isolation         4.242kV (4242V)           Efficiency         -           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, PFC, Standby Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Series	MBC201
Voltage - Input90 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)13.33APower (Watts)160W (200W Forced Air)ApplicationsMedicalVoltage - Isolation4.242kV (4242V)Efficiency-Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, PFC, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Туре	Open Frame
Voltage - Output 2  Voltage - Output 3  Voltage - Output 4  Current - Output (Max)  Applications  Medical  Voltage - Isolation  Efficiency  Operating Temperature  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Size / Dimension  12V	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  Medical  Voltage - Isolation  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  Current - Output 3	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  13.33A  Power (Watts)  Applications  Medical  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Current - Output (Max)  - Current - Output (Max)	Voltage - Output 1	12V
Voltage - Output 4  Current - Output (Max)  13.33A  Power (Watts)  Applications  Medical  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  Medical  Voltage - Isolation  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  13.33A  160W (200W Forced Air)  Medical  4.242kV (4242V)  - Coperating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, PFC, Standby Output, Universal Input  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Output 3	-
Power (Watts)  Applications  Medical  Voltage - Isolation  4.242kV (4242V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Output 4	-
Applications Medical  Voltage - Isolation 4.242kV (4242V)  Efficiency - Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Current - Output (Max)	13.33A
Voltage - Isolation  4.242kV (4242V)  Efficiency  - Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Power (Watts)	160W (200W Forced Air)
Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Applications	Medical
Operating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Isolation	4.242kV (4242V)
Features Adjustable Output, PFC, Standby Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Features	Adjustable Output, PFC, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)
		Report errors?

#### MBC201-1012G Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MBC201-1012G Payment Methods



















### **MBC201-1012G Shipping Methods**













If you have any question about MBC201-1012G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com