



MBC40-1005G Information



For Reference Only

Part Number MBC40-1005G
Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 5.1V 40W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MBC40-1005G Specifications

Manufacturer Part Number MBC40-1005G Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MBC40 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MBC40 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Manufacturer Part Number	MBC40-1005G
Package - Series MBC40 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Manufacturer	Bel Power Solutions
Package - Series MBC40 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MBC40 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 5.1V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 40W Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Series	MBC40
Voltage - Input90 ~ 264 VACVoltage - Output 15.1VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)40WApplicationsMedicalVoltage - Isolation4.242kV (4242V)Efficiency85%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Remote Sense, Standby Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Type	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.1V 5.1V 5.1V 5.1V 5.1V 6.10 6.	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension -000 L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension - 200°L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 1	5.1V
Voltage - Output 4 Current - Output (Max) 8A Power (Watts) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 8A 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 3	-
Power (Watts) Applications Medical Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Output 4	-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Current - Output (Max)	8A
Voltage - Isolation 4.242kV (4242V) Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Power (Watts)	40W
Efficiency 85% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Applications	Medical
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Voltage - Isolation	4.242kV (4242V)
Features Adjustable Output, Remote Sense, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Efficiency	85%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Operating Temperature	$-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)
Size / Dimension 4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)	Features	Adjustable Output, Remote Sense, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 1.20" H (101.6mm x 50.8mm x 30.5mm)
•		Report errors?

MBC40-1005G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MBC40-1005G Payment Methods





















MBC40-1005G Shipping Methods













If you have any question about MBC40-1005G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com