



## MBC41-1012P-2 Information

Heisener.com

Part Number MBC41-1012P-2 Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 12V 40W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MBC41-1012P-2 Specifications**

Manufacturer Part Number         MBC41-1012P-2           Manufacturer         Bel Power Solutions           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MBC41           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         8%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         MBC41           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Manufacturer Part Number	MBC41-1012P-2	
Package         -           Series         MBC41           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Manufacturer	Bel Power Solutions	
Package         -           Series         MBC41           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         MBC41           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)		AC DC Converters	
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Package	-	
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Series	MBC41	
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         3.33A           Power (Watts)         40W           Applications         Medical           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -40°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Type	Open Frame	
Voltage - Output 1       12V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       3.33A         Power (Watts)       40W         Applications       Medical         Voltage - Isolation       4kV (4000V)         Efficiency       85%         Operating Temperature       -40°C ~ 70°C         Features       Universal Input         Mounting Type       Chassis Mount         Size / Dimension       3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -40°C ~ 70°C  Features  Universal Input  Mounting Type  Size / Dimension  Current - Output (Max)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Universal Input Mounting Type Chassis Mount Size / Dimension	Voltage - Output 1	12V	
Voltage - Output 4  Current - Output (Max)  3.33A  Power (Watts)  Applications  Medical  Voltage - Isolation  4kV (4000V)  Efficiency  85%  Operating Temperature  -40°C ~ 70°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension	Voltage - Output 2	-	
Current - Output (Max)  3.33A  Power (Watts)  40W  Applications  Medical  Voltage - Isolation  4kV (4000V)  Efficiency  85%  Operating Temperature  -40°C ~ 70°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Voltage - Output 3	-	
Power (Watts) 40W  Applications Medical  Voltage - Isolation 4kV (4000V)  Efficiency 85%  Operating Temperature -40°C ~ 70°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Voltage - Output 4	-	
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Current - Output (Max)	3.33A	
Voltage - Isolation $4kV$ (4000V) Efficiency $85\%$ Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input Mounting Type Chassis Mount $3.00^{\circ}\text{L} \times 2.00^{\circ}\text{W} \times 0.75^{\circ}\text{H} (76.2\text{mm} \times 50.8\text{mm} \times 19.1\text{mm})$	Power (Watts)	40W	
Efficiency 85%  Operating Temperature $-40^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input  Mounting Type Chassis Mount  Size / Dimension $3.00^{\circ}\text{L} \times 2.00^{\circ}\text{W} \times 0.75^{\circ}\text{H} (76.2\text{mm} \times 50.8\text{mm} \times 19.1\text{mm})$	Applications	Medical	
Operating Temperature -40°C ~ 70°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Voltage - Isolation	4kV (4000V)	
Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Efficiency	85%	
Mounting Type Chassis Mount Size / Dimension 3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Operating Temperature	-40°C ~ 70°C	
Size / Dimension 3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	Features	Universal Input	
	Mounting Type	Chassis Mount	
Report errors?	Size / Dimension	3.00" L x 2.00" W x 0.75" H (76.2mm x 50.8mm x 19.1mm)	
report drois.			Report errors?

### MBC41-1012P-2 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MBC41-1012P-2 Payment Methods


































If you have any question about MBC41-1012P-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com