



MBC550-1T30 Information

Part Number MBC550-1T30 Manufacturer Bel Power Solutions

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 30V 150/550W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MBC550-1T30 Specifications

Manufacturer Part Number MBC550-1T30 Manufacturer Bel Power Solutions Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MBC550 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series MBC550 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Manufacturer Part Number	MBC550-1T30
Package - Series MBC550 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Manufacturer	Bel Power Solutions
Package - Series MBC550 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Category	Power Supplies - External/Internal (Off-Board)
Series MBC550 Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Package	-
Number of Outputs 1 Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Series	MBC550
Voltage - Input 90 ~ 264 VAC Voltage - Output 1 30V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Medical Voltage - Isolation Sefficiency Operating Temperature Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Size / Dimension 30V - Overating Temperature A0°C ~ 70°C Chassis Mount Size / Dimension 30V - Overating Temperature Size / Dimension 30V - Overating Temperature - Overating Temp	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications Medical Voltage - Isolation Site / Dimension Size / Dimension - Output 2 - Current - Output (Max) 5A - Voltage - Isolation Site / Dimension Site / Dimension - Current - Output 4 - Current - Output (Max) 5A - Current - Out	Voltage - Input	90 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) SA Power (Watts) Applications Medical Voltage - Isolation Site / Dimension Size / Dimension - Output (Max) - - - - - - - - - - - - -	Voltage - Output 1	30V
Voltage - Output 4 Current - Output (Max) 5A Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 150W (550W Forced Air) Applications Medical Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Output 3	-
Power (Watts) Applications Medical Voltage - Isolation Significancy Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 150W (550W Forced Air) Medical 3kV (3000V) - COPT C C C C C C C C C C C C C C C C C C C	Voltage - Output 4	-
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Current - Output (Max)	5A
Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature -40°C ~ 70°C Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Power (Watts)	150W (550W Forced Air)
Efficiency -	Applications	Medical
Operating Temperature -40°C ~ 70°C DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Voltage - Isolation	3kV (3000V)
Features DC Input Capable, PFC, Standby Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Operating Temperature	-40°C ~ 70°C
Size / Dimension 5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)	Features	DC Input Capable, PFC, Standby Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.50" H (127.0mm x 76.2mm x 38.1mm)
		Report errors?

MBC550-1T30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MBC550-1T30 Payment Methods



















MBC550-1T30 Shipping Methods













If you have any question about MBC550-1T30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com