



MBR130T3G Information



For Reference Only

Part Number MBR130T3G
Manufacturer ON Semiconductor

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE SCHOTTKY 30V 1A SOD123

Package SOD-123

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MBR130T3G Specifications

Manufacturer Part NumberMBR130T3GManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageSOD-123Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°CReport errors?	Tibility of Specifications	
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageSOD-123Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Manufacturer Part Number	MBR130T3G
PackageDiodes - Rectifiers - SingleSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Manufacturer	ON Semiconductor
PackageSOD-123Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Category	Discrete Semiconductor Products
Series Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case Supplier Device Package Operating Temperature - Junction Schottky 60μ 450mV @ 700mA 500mA 500mA 500mA 60μA @ 30V 6		Diodes - Rectifiers - Single
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io)1AVoltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Package	SOD-123
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 1A Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 60µA @ 30V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package Operating Temperature - Junction 30V 450mV @ 700mA Fast Recovery = < 500ns, > 200mA (Io) - Surface Mount Surface Mount Fackage / Case SOD-123 Supplier Device Package Operating Temperature - Junction -65°C ~ 125°C	Series	-
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 450mV @ 700mA Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 60µA @ 30V Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package Operating Temperature - Junction 1A 450mV @ 700mA 60µA @ 30V - 60µA @ 3	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If450mV @ 700mASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Voltage - DC Reverse (Vr) (Max)	30V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr60μA @ 30VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseSOD-123Supplier Device PackageSOD-123Operating Temperature - Junction-65°C ~ 125°C	Current - Average Rectified (Io)	1A
Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 60μA @ 30V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package SOD-123 Operating Temperature - Junction -65°C ~ 125°C	Voltage - Forward (Vf) (Max) @ If	450mV @ 700mA
Current - Reverse Leakage @ Vr Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package Operating Temperature - Junction 60µA @ 30V - Capacitance @ Vr, F - Capacitance Mount SOD-123 SOD-123 - 65°C ~ 125°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package SOD-123 Operating Temperature - Junction -65°C ~ 125°C	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case SOD-123 Supplier Device Package SOD-123 Operating Temperature - Junction -65°C ~ 125°C	Current - Reverse Leakage @ Vr	60μA @ 30V
Package / Case SOD-123 Supplier Device Package SOD-123 Operating Temperature - Junction -65°C ~ 125°C	Capacitance @ Vr, F	-
Supplier Device Package SOD-123 Operating Temperature - Junction -65°C ~ 125°C	Mounting Type	Surface Mount
Operating Temperature - Junction -65°C ~ 125°C	Package / Case	SOD-123
	Supplier Device Package	SOD-123
Report errors?	Operating Temperature - Junction	-65°C ~ 125°C
		Report errors?

MBR130T3G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MBR130T3G Payment Methods



















MBR130T3G Shipping Methods













If you have any question about MBR130T3G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com