

MBR2550CT

MBR2550CT Information

www.helseng.com	Part Number Manufacturer Category Description Package	MBR2550CT Fairchild/ON Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE ARRAY SCHOTTKY 50V TO220AB TO-220-3 For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBR2550CT Specifications

Manufacturer Fairchild/ON Semiconductor Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Diodes - Rectifiers - Arrays Package TO-220-3 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) SV Current - Average Rectified (Io) (per Diode) 12.5A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr ImA @ 50V Operating Temperature - Junction -65°C ~ 150°C Manufacture Texes -55°C ~ 2000A (Io) Package / Case To-220-3		
CategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Manufacturer Part Number	MBR2550CT
Diodes - Rectifiers - ArraysPackageDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Manufacturer	Fairchild/ON Semiconductor
PackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Package	TO-220-3
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Series	-
Voltage - DC Reverse (Vr) (Max)50VCurrent - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)12.5AVoltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If750mV @ 12.5ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Voltage - DC Reverse (Vr) (Max)	50V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Current - Average Rectified (Io) (per Diode)	12.5A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Voltage - Forward (Vf) (Max) @ If	750mV @ 12.5A
Current - Reverse Leakage @ VrImA @ 50VOperating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-65°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Reverse Recovery Time (trr)	-
Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Current - Reverse Leakage @ Vr	1mA @ 50V
Package / CaseTO-220-3Supplier Device PackageTO-220-3	Operating Temperature - Junction	-65°C ~ 150°C
Supplier Device Package TO-220-3	Mounting Type	Through Hole
	Package / Case	ТО-220-3
Report errors?	Supplier Device Package	TO-220-3
		Report errors?

MBR2550CT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBR2550CT Payment Methods



MBR2550CT Shipping Methods



If you have any question about MBR2550CT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com