

MBR30100CT

MBR30100CT Information

www.helsens.com	 MBR30100CT SMC Diode Solutions Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE ARRAY SCHOTTKY 100V TO220 TO-220-3 For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBR30100CT Specifications

Manufacturer Part NumberMBR30100CTManufacturerSMC Diode SolutionsCategoryDiscret Semiconductor ProductsPackageTo-220-3PackageCDiode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Jo) (per Diode)Schott Secorery = 500ms, > 200mA (TooSpeedSchotvery = 500ms, > 200mA (TooNorder Secorery Time (try)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-SpeedSic C - 150°CMounting Type-Package / CaseToroget HoleSpepier Device PackageTooPackage / CaseTooSpepier Device PackageTooSpepier Device Packa		
CategoryDiscrete Semiconductor ProductsCategoryDiodes - Rectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery = 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220-3	Manufacturer Part Number	MBR30100CT
Index of the sectifiers - ArraysPackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If $850mV @ 15A$ SpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220ABSupplier Device PackageTO-220AB	Manufacturer	SMC Diode Solutions
PackageTO-220-3Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Jo) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220AB	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220AB		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Package	ТО-220-3
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Series	-
Voltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)-Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If850mV @ 15ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - DC Reverse (Vr) (Max)	100V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Average Rectified (Io) (per Diode)	-
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Voltage - Forward (Vf) (Max) @ If	850mV @ 15A
Current - Reverse Leakage @ VrImA @ 100VOperating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Reverse Recovery Time (trr)	-
Mounting TypeThrough HolePackage / CaseTO-220-3Supplier Device PackageTO-220AB	Current - Reverse Leakage @ Vr	1mA @ 100V
Package / CaseTO-220-3Supplier Device PackageTO-220AB	Operating Temperature - Junction	$-55^{\circ}C \sim 150^{\circ}C$
Supplier Device Package TO-220AB	Mounting Type	Through Hole
	Package / Case	TO-220-3
	Supplier Device Package	TO-220AB
Report err		Report errors?

MBR30100CT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBR30100CT Payment Methods



MBR30100CT Shipping Methods



If you have any question about MBR30100CT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com