

MBRB16H60HE3/81

MBRB16H60HE3/81 Information

www.hersener.com	 MBRB16H60HE3/81 Vishay Semiconductor Diodes Division Discrete Semiconductor Products Diodes - Rectifiers - Single DIODE SCHOTTKY 60V 16A TO263AB TO-263-3, D2Pak (2 Leads + Tab), TO-263AB For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBRB16H60HE3/81 Specifications

ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABOperating Temperature - Junction-65°C ~ 175°C		
CategoryDiscrete Semiconductor Products Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (ttr)-Current - Reverse Leakage @ Vr100µA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	MBRB16H60HE3/81
Diodes - Rectifiers - SinglePackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeries-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100 μ A @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Manufacturer	Vishay Semiconductor Diodes Division
Package TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Series - Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) 16A Voltage - Forward (Vf) (Max) @ If 730mV @ 16A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 100µA @ 60V Capacitance @ Vr, F - Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package TO-263AB Operating Temperature - Junction -55°C ~ 175°C	Category	Discrete Semiconductor Products
Series-Series-Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max) $60V$ Current - Average Rectified (Io) $16A$ Voltage - Forward (Vf) (Max) @ If $730mV @ 16A$ SpeedFast Recovery =< $500ns, > 200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $100\muA @ 60V$ Current - Reverse Leakage @ Vr-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100µA @ 60VCurrent - Reverse Leakage @ Vr-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Voltage - DC Reverse (Vr) (Max)60VCurrent - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Series	-
Current - Average Rectified (Io)16AVoltage - Forward (Vf) (Max) @ If730mV @ 16ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If $730mV @ 16A$ SpeedFast Recovery =< $500ns$, > $200mA$ (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr $100\muA @ 60V$ Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	60V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	16A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr100μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	730mV @ 16A
Current - Reverse Leakage @ Vr100μA @ 60VCapacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F-Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Reverse Recovery Time (trr)	-
Mounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Current - Reverse Leakage @ Vr	100µA @ 60V
Package / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Capacitance @ Vr, F	-
Supplier Device PackageTO-263ABOperating Temperature - Junction-65°C ~ 175°C	Mounting Type	Surface Mount
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
	Supplier Device Package	TO-263AB
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
1		Report errors?

MBRB16H60HE3/81 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRB16H60HE3/81 Payment Methods





If you have any question about MBRB16H60HE3/81, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com