

MBRB20H100CTT4G

MBRB20H100CTT4G Information



For Reference Only

Part Number MBRB20H100CTT4G
Manufacturer ON Semiconductor

Category Discrete Semiconductor Products
Diodes - Rectifiers - Arrays

DescriptionDIODE ARRAY SCHOTTKY 100V D2PAK**Package**TO-263-3, D2Pak (2 Leads + Tab), TO-263AB

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MBRB20H100CTT4G Specifications

Manufacturer Part NumberMBRB20H100CTT4GManufacturerON SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesSWITCHMODE?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3		
Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Package TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Series SWITCHMODE? Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 100V Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 770mV @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 4.5µA @ 100V Operating Temperature - Junction -65°C ~ 175°C Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package	Manufacturer Part Number	MBRB20H100CTT4G
Diodes - Rectifiers - ArraysPackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesSWITCHMODE?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3	Manufacturer	ON Semiconductor
PackageTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSeriesSWITCHMODE?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3	Category	Discrete Semiconductor Products
SeriesSWITCHMODE?Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)100VCurrent - Average Rectified (Io) (per Diode)10AVoltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3	Package	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 4.5μA @ 100V Operating Temperature - Junction -65°C ~ 175°C Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package	Series	SWITCHMODE?
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) 10A Voltage - Forward (Vf) (Max) @ If 770mV @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 4.5μA @ 100V Operating Temperature - Junction -65°C ~ 175°C Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 770mV @ 10A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr 4.5µA @ 100V Operating Temperature - Junction -65°C ~ 175°C Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK-3	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If770mV @ 10ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3	Voltage - DC Reverse (Vr) (Max)	100V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr4.5μA @ 100VOperating Temperature - Junction-65°C ~ 175°CMounting TypeSurface MountPackage / CaseTO-263-3, D2Pak (2 Leads + Tab), TO-263ABSupplier Device PackageD2PAK-3	Current - Average Rectified (Io) (per Diode)	10A
Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr $4.5\mu A$ @ $100V$ Operating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$ Mounting Type Surface Mount Package / Case $TO-263-3$, $D2Pak$ (2 Leads + Tab), $TO-263AB$ Supplier Device Package $D2PAK-3$	Voltage - Forward (Vf) (Max) @ If	770mV @ 10A
Current - Reverse Leakage @ Vr $4.5\mu A$ @ $100V$ Operating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$ Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction -65°C ~ 175°C Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK-3	Reverse Recovery Time (trr)	-
Mounting Type Surface Mount Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK-3	Current - Reverse Leakage @ Vr	4.5μA @ 100V
Package / Case TO-263-3, D2Pak (2 Leads + Tab), TO-263AB Supplier Device Package D2PAK-3	Operating Temperature - Junction	-65°C ~ 175°C
Supplier Device Package D2PAK-3	Mounting Type	Surface Mount
	Package / Case	TO-263-3, D2Pak (2 Leads + Tab), TO-263AB
Report errors?	Supplier Device Package	D2PAK-3
Report errors.		Report errors?

MBRB20H100CTT4G Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRB20H100CTT4G Payment Methods



















MBRB20H100CTT4G Shipping Methods













If you have any question about MBRB20H100CTT4G, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com