

MBRD1060CTTR

MBRD1060CTTR Information



For Reference Only

Part Number MBRD1060CTTR
Manufacturer SMC Diode Solutions

Category Discrete Semiconductor Products
Diodes - Rectifiers - Arrays

DescriptionDIODE ARRAY SCHOTTKY 60V DPAK**Package**TO-252-3, DPak (2 Leads + Tab), SC-63

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MBRD1060CTTR Specifications

Manufacturer Part Number Manufacturer SMC Diode Solutions Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If Fast Recovery =< 500ns, > 200mA (Io)
Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Diodes - Rectifiers - Arrays Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Package TO-252-3, DPak (2 Leads + Tab), SC-63 Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) - Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Series - Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) - Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Diode Configuration 1 Pair Common Cathode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 60V Current - Average Rectified (Io) (per Diode) - Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Diode Type Schottky Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Current - Average Rectified (Io) (per Diode) Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
Voltage - Forward (Vf) (Max) @ If 700mV @ 5A
-
Speed Fast Recovery =< 500ns, > 200mA (Io)
Reverse Recovery Time (trr) -
Current - Reverse Leakage @ Vr 1mA @ 60V
Operating Temperature - Junction $-55^{\circ}\text{C} \sim 150^{\circ}\text{C}$
Mounting Type Surface Mount
Package / Case TO-252-3, DPak (2 Leads + Tab), SC-63
Supplier Device Package DPAK
Report errors?

MBRD1060CTTR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRD1060CTTR Payment Methods



















MBRD1060CTTR Shipping Methods













If you have any question about MBRD1060CTTR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com