

## **MBRF20045**

## **MBRF20045** Information

Www.heisenercom	Part Number Manufacturer Category Description Package	MBRF20045 GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE SCHOTTKY 45V 100A TO244AB TO-244AB For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **MBRF20045** Specifications

Manufacturer Part NumberMBRF20045ManufacturerGeneSiC SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery = 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis Mount	
CategoryDiscrete Semiconductor ProductsCategoryDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
NumberDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery = 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Package   TO-244AB     Series   -     Diode Configuration   1 Pair Common Cathode     Diode Type   Schottky     Voltage - DC Reverse (Vr) (Max)   45V     Current - Average Rectified (Io) (per Diode)   100A     Voltage - Forward (Vf) (Max) @ If   700mV @ 100A     Speed   Fast Recovery =< 500ns, > 200mA (Io)     Reverse Recovery Time (trr)   -     Current - Reverse Leakage @ Vr   ImA @ 45V     Operating Temperature - Junction   -55°C ~ 150°C	
Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If70mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Diode Type Schottky   Voltage - DC Reverse (Vr) (Max) $45V$ Current - Average Rectified (Jo) (per Diode) $100A$ Voltage - Forward (Vf) (Max) @ If $70mV @ 100A$ Speed Fast Recovery =< 500ns, > 200mA (Jo)   Reverse Recovery Time (trr) $-$ Current - Reverse Leakage @ Vr ImA @ 45V   Operating Temperature - Junction $-55^\circ$ C ~ 150°C	
Voltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Current - Average Rectified (Io) (per Diode)100AVoltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Voltage - Forward (Vf) (Max) @ If700mV @ 100ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Current - Reverse Leakage @ Vr1mA @ 45VOperating Temperature - Junction-55°C ~ 150°C	
Operating Temperature - Junction $-55^{\circ}C \sim 150^{\circ}C$	
Mounting Type Chassis Mount	
Chussis Hound	
Package / Case TO-244AB	
Supplier Device Package TO-244AB	
Repo	t errors?

### **MBRF20045** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

## SERVICE SUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

# MBRF20045 Payment Methods

## **MBRF20045** Shipping Methods



If you have any question about MBRF20045, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com