

MBRF30040

MBRF30040 Information

Www.heisenencom	Part Number Manufacturer Category Description Package	MBRF30040 GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE SCHOTTKY 40V 150A TO244AB TO-244AB	
	-	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBRF30040 Specifications

Manufacturer Part NumberMBRF30040ManufacturerGeneSiC SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode ConfigurationI Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Jo) (per Diode)150ASpeedFast Recovery Time (trr)Speed-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55° C ~ 150°CMounting TypeChasis MountPackage / CaseTO-244ABSupplier Device PackageTO-244ABSupplier Device PackageTO-244ABSuppli		
CategoryDiscrete Semiconductor ProductsCategoryDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode ConfigurationI Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery = <500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Manufacturer Part Number	MBRF30040
IndexDiodes - Rectifiers - ArraysPackageTO-244ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If70mV @ 150ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Manufacturer	GeneSiC Semiconductor
PackageTO-244ABSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If70mV @ 150ASpeedFast Recovery = <500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Package	TO-244AB
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)40VCurrent - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Series	-
Voltage - DC Reverse (Vr) (Max) 40V Current - Average Rectified (Io) (per Diode) 150A Voltage - Forward (Vf) (Max) @ If 700mV @ 150A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr ImA @ 40V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Chassis Mount Package / Case TO-244AB Supplier Device Package TO-244AB	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)150AVoltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If700mV @ 150ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Voltage - DC Reverse (Vr) (Max)	40V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Current - Average Rectified (Io) (per Diode)	150A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Voltage - Forward (Vf) (Max) @ If	700mV @ 150A
Current - Reverse Leakage @ VrImA @ 40VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Reverse Recovery Time (trr)	-
Mounting TypeChassis MountPackage / CaseTO-244ABSupplier Device PackageTO-244AB	Current - Reverse Leakage @ Vr	1mA @ 40V
Package / CaseTO-244ABSupplier Device PackageTO-244AB	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package TO-244AB	Mounting Type	Chassis Mount
	Package / Case	TO-244AB
Report erro	Supplier Device Package	TO-244AB
		Report errors?

MBRF30040 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRF30040 Payment Methods



MBRF30040 Shipping Methods



If you have any question about MBRF30040, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com