

MBRTA60030RL

MBRTA60030RL Information

WWW.Horser	 MBRTA60030RL GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE SCHOTTKY 30V 300A 3TOWER Three Tower For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBRTA60030RL Specifications

Manufacturer GeneSic Semiconductor Category Discrete Semiconductor Products Diodes - Rectifiers - Arrays Diodes - Rectifiers - Arrays Package Three Tower Series - Diode Configuration 1 Pair Common Anode Diode Type Schottky Voltage - DC Reverse (Vr) (Max) 30V Current - Average Rectified (Io) (per Diode) 300A Voltage - Forward (Vf) (Max) @ If StomV @ 300A Speed Fast Recovery = 500ms, > 200mA (Io) Reverse Recovery Time (trr) - Current - Reverse Leakage @ Vr ImA @ 30V Operating Temperature - Junction -55°C ~ 150°C Mounting Type Chassis Mount		
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer Part Number	MBRTA60030RL
Diodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer	GeneSiC Semiconductor
PackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ IfS80mV @ 300ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common AnodeDiode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ IfS80mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Package	Three Tower
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Series	-
Voltage - DC Reverse (Vr) (Max)30VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Configuration	1 Pair Common Anode
Current - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If580mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - DC Reverse (Vr) (Max)	30V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Average Rectified (Io) (per Diode)	300A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - Forward (Vf) (Max) @ If	580mV @ 300A
Current - Reverse Leakage @ VrImA @ 30VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Reverse Recovery Time (trr)	-
Mounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Reverse Leakage @ Vr	1mA @ 30V
Package / Case Three Tower Supplier Device Package Three Tower	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package Three Tower	Mounting Type	Chassis Mount
	Package / Case	Three Tower
Report errors?	Supplier Device Package	Three Tower
		Report errors?

MBRTA60030RL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRTA60030RL Payment Methods



MBRTA60030RL Shipping Methods



If you have any question about MBRTA60030RL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com