

MBRTA60045L

MBRTA60045L Information

For Reference Only	Part Number Manufacturer Category Description Package	MBRTA60045L GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE SCHOTTKY 45V 300A 3TOWER Three Tower	
	Раскаде	For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBRTA60045L Specifications

Manufacturer Part NumberMBRTA60045LManufacturerGeneSiC SemiconductorCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Jo) (per Diode)300ASpeedFast Recovery Time (trr)Series Recovery Time (trr)-Current - Reverse Leakage @ VrSma @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseThree TowerPackage / CaseThree Tower		
CategoryDiscrete Semiconductor ProductsCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode ConfigurationI Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery = <500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrSmA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer Part Number	MBRTA60045L
Diddes - Rectifiers - ArraysPackageDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode ConfigurationI Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-SrS°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer	GeneSiC Semiconductor
PackageThree TowerSeries-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Jo) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery = < 500ms, > 200mA (Jo)Reverse Recovery Time (trrr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseThree TowerSupplier Device PackageThree TowerSupplier Device PackageThree Tower	Category	Discrete Semiconductor Products
Series-Series-Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery = < 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseThree TowerSupplier Device PackageThree Tower		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common CathodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Package	Three Tower
Diode TypeSchottkyVoltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Series	-
Voltage - DC Reverse (Vr) (Max)45VCurrent - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Configuration	1 Pair Common Cathode
Current - Average Rectified (Io) (per Diode)300AVoltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery = < 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If600mV @ 300ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - DC Reverse (Vr) (Max)	45V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Average Rectified (Io) (per Diode)	300A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - Forward (Vf) (Max) @ If	600mV @ 300A
Current - Reverse Leakage @ Vr5mA @ 45VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Reverse Recovery Time (trr)	-
Mounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Reverse Leakage @ Vr	5mA @ 45V
Package / Case Three Tower Supplier Device Package Three Tower	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package Three Tower	Mounting Type	Chassis Mount
	Package / Case	Three Tower
	Supplier Device Package	Three Tower
Report error		Report errors?

MBRTA60045L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRTA60045L Payment Methods



MBRTA60045L Shipping Methods



If you have any question about MBRTA60045L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com