

MBRTA80020R

MBRTA80020R Information

WWW.INSSEE	Part Number Manufacturer Category Description Package	MBRTA80020R GeneSiC Semiconductor Discrete Semiconductor Products Diodes - Rectifiers - Arrays DIODE SCHOTTKY 20V 400A 3TOWER Three Tower For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MBRTA80020R Specifications

ManufacturerGeneSic SemiconductorCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChasis MountPackage / CaseThree TowerSupplier Device PackageThree Tower		
CategoryDiscrete Semiconductor ProductsCategoryDiscrete Semiconductor ProductsPackageDiodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer Part Number	MBRTA80020R
Diodes - Rectifiers - ArraysPackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Manufacturer	GeneSiC Semiconductor
PackageThree TowerSeries-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Category	Discrete Semiconductor Products
Series-Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ms, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower		Diodes - Rectifiers - Arrays
Diode Configuration1 Pair Common AnodeDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Package	Three Tower
Diode TypeSchottkyDiode TypeSchottkyVoltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Series	-
Voltage - DC Reverse (Vr) (Max)20VCurrent - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Configuration	1 Pair Common Anode
Current - Average Rectified (Io) (per Diode)400AVoltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Diode Type	Schottky
Voltage - Forward (Vf) (Max) @ If720mV @ 400ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - DC Reverse (Vr) (Max)	20V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Average Rectified (Io) (per Diode)	400A
Reverse Recovery Time (trr)-Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Voltage - Forward (Vf) (Max) @ If	720mV @ 400A
Current - Reverse Leakage @ VrImA @ 20VOperating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Operating Temperature - Junction-55°C ~ 150°CMounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Reverse Recovery Time (trr)	-
Mounting TypeChassis MountPackage / CaseThree TowerSupplier Device PackageThree Tower	Current - Reverse Leakage @ Vr	1mA @ 20V
Package / Case Three Tower Supplier Device Package Three Tower	Operating Temperature - Junction	-55°C ~ 150°C
Supplier Device Package Three Tower	Mounting Type	Chassis Mount
	Package / Case	Three Tower
Report errors?	Supplier Device Package	Three Tower
		Report errors?

MBRTA80020R Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MBRTA80020R Payment Methods



MBRTA80020R Shipping Methods



If you have any question about MBRTA80020R, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com