



MC74LCX14DTG Information



For Reference Only

Part Number MC74LCX14DTG

Manufacturer ON Semiconductor

Category Integrated Circuits (ICs)
Logic - Gates and Inverters

Description IC INVERT HEX SCHM 5VIN 14-TSSOP

Package 14-TSSOP (0.173", 4.40mm Width)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MC74LCX14DTG Specifications

Manufacturer Part Number MC74LCX14DTG Manufacturer ON Semiconductor Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74LCX Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features Schmitt Trigger Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10µA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.4 V ~ 0.6 V Logic Level - High 1.7 V ~ 2.2 V Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount		
Category Integrated Circuits (ICs) Logic - Gates and Inverters Package 14-TSSOP (0.173", 4.40mm Width) Series 74LCX Logic Type Inverter Number of Circuits 6 Number of Inputs 6 Features Schmitt Trigger Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10μA Current - Output High, Low 24mA, 24mA Logic Level - Low 0.4 V ~ 0.6 V Logic Level - High 1.7 V ~ 2.2 V Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Manufacturer Part Number	MC74LCX14DTG
PackageLogic - Gates and InvertersPackage $14\text{-TSSOP}(0.173", 4.40\text{mm Width})$ Series 74LCX Logic TypeInverterNumber of Circuits 6 Number of Inputs 6 FeaturesSchmitt TriggerVoltage - Supply $2\text{ V} \sim 3.6\text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low $24\text{mA}, 24\text{mA}$ Logic Level - Low $0.4\text{ V} \sim 0.6\text{ V}$ Logic Level - High $1.7\text{ V} \sim 2.2\text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ $3.3\text{V}, 50\text{pF}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Manufacturer	ON Semiconductor
Package14-TSSOP (0.173", 4.40mm Width)Series74LCXLogic TypeInverterNumber of Circuits6Number of Inputs6FeaturesSchmitt TriggerVoltage - Supply2 V ~ 3.6 VCurrent - Quiescent (Max) 10μ ACurrent - Output High, Low $24m$ A, $24m$ ALogic Level - Low $0.4 V ~ 0.6 V$ Logic Level - High $1.7 V ~ 2.2 V$ Max Propagation Delay @ V, Max CL $6.5ns$ @ $3.3V$, $50p$ FOperating Temperature -40 °C ~ 85 °CMounting TypeSurface Mount	Category	Integrated Circuits (ICs)
Series $74LCX$ Logic TypeInverterNumber of Circuits6Number of Inputs6FeaturesSchmitt TriggerVoltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.4 \text{ V} \sim 0.6 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount		Logic - Gates and Inverters
Logic TypeInverterNumber of Circuits6Number of Inputs6FeaturesSchmitt TriggerVoltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.4 \text{ V} \sim 0.6 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Package	14-TSSOP (0.173", 4.40mm Width)
Number of Circuits6Number of Inputs6FeaturesSchmitt TriggerVoltage - Supply $2 \text{ V} \sim 3.6 \text{ V}$ Current - Quiescent (Max) $10\mu\text{A}$ Current - Output High, Low 24mA , 24mA Logic Level - Low $0.4 \text{ V} \sim 0.6 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Series	74LCX
Number of Inputs 6 Features Schmitt Trigger Voltage - Supply 2 V ~ 3.6 V Current - Quiescent (Max) 10 μ A Current - Output High, Low 24mA, 24mA Logic Level - Low 0.4 V ~ 0.6 V Logic Level - High 1.7 V ~ 2.2 V Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Logic Type	Inverter
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Number of Circuits	6
Voltage - Supply $2\ V \sim 3.6\ V$ $Current - Quiescent (Max) 10\mu A$ $Current - Output High, Low 24mA, 24mA$ $Logic Level - Low 0.4\ V \sim 0.6\ V$ $Logic Level - High 1.7\ V \sim 2.2\ V$ $Max\ Propagation\ Delay\ @\ V,\ Max\ CL 6.5ns\ @\ 3.3V,\ 50pF$ $Operating\ Temperature -40^{\circ}C \sim 85^{\circ}C$ $Mounting\ Type Surface\ Mount$	Number of Inputs	6
Current - Quiescent (Max) $10\mu A$ Current - Output High, Low $24mA, 24mA$ Logic Level - Low $0.4 \ V \sim 0.6 \ V$ Logic Level - High $1.7 \ V \sim 2.2 \ V$ Max Propagation Delay @ V, Max CL $6.5ns \ @ \ 3.3V, 50pF$ Operating Temperature $-40^{\circ}C \sim 85^{\circ}C$ Mounting Type Surface Mount	Features	Schmitt Trigger
Current - Output High, Low 24mA , 24mA Logic Level - Low $0.4 \text{ V} \sim 0.6 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Voltage - Supply	2 V ~ 3.6 V
Logic Level - Low $0.4 \text{ V} \sim 0.6 \text{ V}$ Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Quiescent (Max)	10μΑ
Logic Level - High $1.7 \text{ V} \sim 2.2 \text{ V}$ Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V , 50pF Operating Temperature $-40 ^{\circ}\text{C} \sim 85 ^{\circ}\text{C}$ Mounting TypeSurface Mount	Current - Output High, Low	24mA, 24mA
Max Propagation Delay @ V, Max CL 6.5ns @ 3.3V, 50pF Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount	Logic Level - Low	0.4 V ~ 0.6 V
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Mounting Type Surface Mount	Logic Level - High	1.7 V ~ 2.2 V
Mounting Type Surface Mount	Max Propagation Delay @ V, Max CL	6.5ns @ 3.3V, 50pF
	Operating Temperature	-40°C ~ 85°C
	Mounting Type	Surface Mount
Supplier Device Package 14-TSSOP	Supplier Device Package	14-TSSOP
Package / Case 14-TSSOP (0.173", 4.40mm Width)	Package / Case	14-TSSOP (0.173", 4.40mm Width)
Report errors?		Report errors?

MC74LCX14DTG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MC74LCX14DTG Payment Methods





















MC74LCX14DTG Shipping Methods













If you have any question about MC74LCX14DTG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com