

MCT5211TVM

MCT5211TVM Information

www.heisener.com	Part Number Manufacturer Category Description Package	Isolators Optoisolators - Transistor, Photovoltaic Output OPTOISO 4.17KV TRANS W/BASE 6DIP 6-DIP (0.400", 10.16mm) For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote
	www.heisener.com For Reference Only	www.helsener.com Description Package	Manufacturer Fairchild/ON Semiconductor Category Isolators Optoisolators - Transistor, Photovoltaic Output Description OPTOISO 4.17KV TRANS W/BASE 6DIP Package 6-DIP (0.400", 10.16mm) For Reference Only Website: https://www.heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MCT5211TVM Specifications

Manufacturer Part NumberMCT5211TVMManufacturerFairchild/ON SemiconductorCategoryIsolatorsCategoryOptoisolators - Transistor, Photovoltaic OutputPackage6-DIP (0.400", 10.16mm)Series-Number of Channels1Voltage - Isolation150% @ 1.6mACurrent Transfer Ratio (Mar)-Current Transfer Ratio (Mar)-Fun On / Turn Off Time (Typ)-Res / Fall Time (Typ)-
CategoryIsolatorsCategoryOptoisolators - Transistor, Photovoltaic OutputPackage6-DIP (0.400", 10.16mm)Series-Number of Channels1Voltage - Isolation4170VrmsCurrent Transfer Ratio (Max)-Current Transfer Ratio (Max)-Tun On / Turn Off Time (Typ)14µs, 2.5µs
Optoisolators - Transistor, Photovoltaic OutputPackage6-DIP (0.400", 10.16mm)Series-Number of Channels1Voltage - Isolation4170VrmsCurrent Transfer Ratio (Min)150% @ 1.6mACurrent Transfer Ratio (Max)-Turn On / Turn Off Time (Typ)14µs, 2.5µs
Package 6-DIP (0.400", 10.16mm) Series - Number of Channels 1 Voltage - Isolation 4170Vrms Current Transfer Ratio (Min) 150% @ 1.6mA Current Transfer Ratio (Max) - Turn On / Turn Off Time (Typ) 14µs, 2.5µs
Series - Number of Channels 1 Voltage - Isolation 4170Vrms Current Transfer Ratio (Min) 150% @ 1.6mA Current Transfer Ratio (Max) - Turn On / Turn Off Time (Typ) 14µs, 2.5µs
Number of Channels1Voltage - Isolation4170VrmsCurrent Transfer Ratio (Min)150% @ 1.6mACurrent Transfer Ratio (Max)-Turn On / Turn Off Time (Typ)14µs, 2.5µs
Voltage - Isolation4170VrmsCurrent Transfer Ratio (Min)150% @ 1.6mACurrent Transfer Ratio (Max)-Turn On / Turn Off Time (Typ)14µs, 2.5µs
Current Transfer Ratio (Min)150% @ 1.6mACurrent Transfer Ratio (Max)-Turn On / Turn Off Time (Typ)14µs, 2.5µs
Current Transfer Ratio (Max)-Turn On / Turn Off Time (Typ)14µs, 2.5µs
Turn On / Turn Off Time (Typ) 14µs, 2.5µs
Rise / Fall Time (Typ) -
Input Type DC
Output Type Transistor with Base
Voltage - Output (Max) 30V
Current - Output / Channel 150mA
Voltage - Forward (Vf) (Typ) 1.25V
Current - DC Forward (If) (Max) 50mA
Vce Saturation (Max) 400mV
Operating Temperature $-40^{\circ}\text{C} \sim 100^{\circ}\text{C}$
Mounting Type Through Hole
Package / Case 6-DIP (0.400", 10.16mm)
Supplier Device Package 6-DIP
Report errors

MCT5211TVM Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MCT5211TVM Payment Methods





If you have any question about MCT5211TVM, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com