

## **MD-30SMK Information**

www.heisener.com

For Reference Only

**Part Number** MD-30SMK **Manufacturer** CUI Inc.

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN MINI-DIN 3POS FEMALE SHIELD

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MD-30SMK Specifications**

Manufacturer Part Number       MD-30SMK         Manufacturer       CUI Inc.         Category       Connectors, Interconnects         Package       -         Series       MD         Connector Type       Receptacle, Female Sockets         Number of Positions       3         Shell Size - Insert       Mini DIN         Shell Size, MIL       -         Mounting Type       Through Hole, Right Angle         Termination       Solder         Fastening Type       Push-Pull         Orientation       Keyed         Ingress Protection       -         Shell Material, Finish       Polybutylene Terephthalate (PBT)         Contact Finish       Silver         Features       Board Lock, Shielded         Voltage - Rated       100VAC, 12VDC         Current Rating       1A, 2A		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Manufacturer Part Number	MD-30SMK
Package-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Manufacturer	CUI Inc.
Package-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Category	Connectors, Interconnects
SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Package	-
Number of Positions3Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Series	MD
Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesBoard Lock, ShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull Orientation Keyed  Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Board Lock, Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Number of Positions	3
Mounting Type Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Board Lock, Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Size - Insert	Mini DIN
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Board Lock, Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Size, MIL	-
Fastening Type Push-Pull  Orientation Keyed  Ingress Protection -  Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Board Lock, Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Mounting Type	Through Hole, Right Angle
Orientation Keyed  Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Board Lock, Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Termination	Solder
Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Board Lock, Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Fastening Type	Push-Pull
Shell Material, Finish  Contact Finish  Silver  Features  Board Lock, Shielded  Voltage - Rated  100VAC, 12VDC  Current Rating  1A, 2A	Orientation	Keyed
Contact Finish  Features  Board Lock, Shielded  Voltage - Rated  100VAC, 12VDC  Current Rating  1A, 2A	Ingress Protection	-
Features Board Lock, Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Shell Material, Finish	Polybutylene Terephthalate (PBT)
Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Contact Finish	Silver
Current Rating 1A, 2A	Features	Board Lock, Shielded
	Voltage - Rated	100VAC, 12VDC
Report errors?	Current Rating	1A, 2A
		Report errors?

#### **MD-30SMK Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MD-30SMK Payment Methods**



















### **MD-30SMK Shipping Methods**













If you have any question about MD-30SMK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com