

### **MD-60SM Information**



For Reference Only

**Part Number** MD-60SM **Manufacturer** CUI Inc.

Category Connectors, Interconnects Circular Connectors

**Description** CONN MINI-DIN 6 PIN FEMALE PCB

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MD-60SM Specifications**

Manufacturer Part NumberMD-60SMManufacturerCUI Inc.CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A		
Category Circular Connectors Circular Connectors  Package - Series MD Connector Type Receptacle, Female Sockets Number of Positions 6 Shell Size - Insert Mini DIN Shell Size, MIL - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Shielded Voltage - Rated Lurrent Rating  Connectors, Interconnects Circular Connectors  AD Connectors Interconnectors  AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors Interconnectors AD Connectors AD Connector	Manufacturer Part Number	MD-60SM
Package-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Manufacturer	CUI Inc.
Package-SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Category	Connectors, Interconnects
SeriesMDConnector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Package	-
Number of Positions6Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Series	MD
Shell Size - InsertMini DINShell Size, MIL-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress Protection-Shell Material, FinishPolybutylene Terephthalate (PBT)Contact FinishSilverFeaturesShieldedVoltage - Rated100VAC, 12VDCCurrent Rating1A, 2A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull Orientation Keyed  Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Number of Positions	6
Mounting Type Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Size - Insert	Mini DIN
Termination Solder Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT) Contact Finish Silver Features Shielded Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Mounting Type	Through Hole, Right Angle
Orientation Keyed  Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Termination	Solder
Ingress Protection - Shell Material, Finish Polybutylene Terephthalate (PBT)  Contact Finish Silver  Features Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Fastening Type	Push-Pull
Shell Material, Finish  Contact Finish  Silver  Features  Shielded  Voltage - Rated  100VAC, 12VDC  Current Rating  1A, 2A	Orientation	Keyed
Contact Finish  Features  Shielded  Voltage - Rated  Current Rating  Silver  Shielded  100VAC, 12VDC  1A, 2A	Ingress Protection	-
Features Shielded  Voltage - Rated 100VAC, 12VDC  Current Rating 1A, 2A	Shell Material, Finish	Polybutylene Terephthalate (PBT)
Voltage - Rated 100VAC, 12VDC Current Rating 1A, 2A	Contact Finish	Silver
Current Rating 1A, 2A	Features	Shielded
	Voltage - Rated	100VAC, 12VDC
Report errors?	Current Rating	1A, 2A
		Report errors?

### **MD-60SM Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MD-60SM Payment Methods**



















## **MD-60SM Shipping Methods**













If you have any question about MD-60SM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com